# Product data sheet

Specification





# TeSys F contactor - 3P (3 NO) - AC-3 - <= 440 V 115 A - coil 600 V AC

LC1F115X6

! Discontinued on: Jan 23, 2021

(!) Discontinued

#### Main

Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Resistive load Motor control	
Utilisation Category	AC-1 AC-4 AC-3	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	600 V AC 40400 Hz	
[le] Rated Operational Current	200 A (at <104 °F (40 °C)) at <= 440 V AC-1 115 A (at <131 °F (55 °C)) at <= 440 V AC-3	

#### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	200 A (at 104 °F (40 °C))
Rated Breaking Capacity	920 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1100 A 104 °F (40 °C) - 10 s 640 A 104 °F (40 °C) - 30 s 520 A 104 °F (40 °C) - 1 min 400 A 104 °F (40 °C) - 3 min 320 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	125 A aM at <= 440 V 200 A gG at <= 440 V
Average Impedance	0.37 mOhm - Ith 200 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	15 W AC-1 5 W AC-3
Overvoltage Category	III
Power Pole Contact Composition	3 NO

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Motor Power Kw	55 kW at 380400 V AC 50/60 Hz (AC-3) 59 kW at 415 V AC 50/60 Hz (AC-3) 59 kW at 440 V AC 50/60 Hz (AC-3) 75 kW at 500 V AC 50/60 Hz (AC-3) 80 kW at 660690 V AC 50/60 Hz (AC-3) 30 kW at 220230 V AC 50/60 Hz (AC-3) 18.5 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Voltage Limits	Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C)) Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In Va	660 VA, 60 Hz 0.3 68 °F (20 °C))
Hold-In Power Consumption In Va	55 VA, 60 Hz 0.3 68 °F (20 °C))
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)
Operating Time	2335 ms closing 515 ms opening
Connections - Terminals	Power circuit bar 2 20 x 3 mm  Power circuit lugs-ring terminals 1 0.15 in² (95 mm²)  Power circuit connector 1 0.15 in² (95 mm²)  Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without cable end  Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end  Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end  Power circuit bolted connection
Tightening Torque	Power circuit 88.51 lbf.in (10 N.m) Control circuit 10.62 lbf.in (1.2 N.m)
Mounting Support	Plate
Heat Dissipation	1216 W
Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JIS C8201-4-1
Product Certifications	RINA RMRoS ABS LROS (Lloyds register of shipping) BV UL CB DNV CCC
Compatibility Code	LC1F
Control Circuit Type	AC 60 Hz
Environment	
Ip Degree Of Protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	23131 °F (-555 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Darmissible Ambient Air	40 450 05 (40 50 00)

-40...158 °F (-40...70 °C)

Permissible Ambient Air Temperature Around The Device

Height	6.38 in (162 mm)
Width	6.43 in (163.3 mm)
Depth	6.73 in (171 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	7.56 lb(US) (3.43 kg)

## Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	112
Gtin	3389110459869
Returnability	No

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

### **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

	Mercury Free	
	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov