# **Product data sheet**

Specifications





TeSys F contactor - 3P (3 NO) - AC-1 - <= 690 V 1260 A - coil 380 V AC

LC1F1250Q7

! Discontinued on: Jul 12, 2021

#### (!) Discontinued

#### Main

Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	3P
[Ue] Rated Operational Voltage	<= 460 V DC <= 690 V AC 50/60 Hz
[Uc] Control Circuit Voltage	380 V AC 40400 Hz
[le] Rated Operational Current	1260 A (at <104 °F (40 °C)) AC-1

### Complementary

J	
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	1260 A (at 104 °F (40 °C))
Rated Breaking Capacity	1890 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	3000 A 104 °F (40 °C) - 3 min 8000 A 104 °F (40 °C) - 10 s 5200 A 104 °F (40 °C) - 30 s 4000 A 104 °F (40 °C) - 1 min 2000 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	1000 A gG at <= 440 V
Average Impedance	0.12 mOhm - Ith 1260 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	120 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	3 NO
Control Circuit Voltage Limits	Operational 0.851.1 Uc 40400 Hz 131 °F (55 °C)) Drop-out 0.250.5 Uc 40400 Hz 131 °F (55 °C))
Inrush Power In Va	1650 VA, 40400 Hz 0.9 68 °F (20 °C))
Hold-In Power Consumption In Va	22 VA, 40400 Hz 0.9 68 °F (20 °C))
Maximum Operating Rate	1200 cyc/h 131 °F (55 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Operating Time	4080 ms closing 100200 ms opening
	100200 fils opening
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid without cable end
	Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end
	Power circuit bar 2 100 x 5 mm
	Power circuit bolted connection
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m)
	Power circuit 513.34 lbf.in (58 N.m)
Mounting Support	Plate
Heat Dissipation	20 W
Standards	IEC 60947-4-1
	JIS C8201-4-1
	IEC 60947-1
	EN 60947-4-1
	EN 60947-1
Product Certifications	СВ
	UL
	CSA
	CQC
	CE
	UKCA
	CCC
Compatibility Code	LC1F
Control Circuit Type	AC 40400 Hz

### **Environment**

Protective Treatment	тн
Ambient Air Temperature For Operation	23104 °F (-540 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	-40140 °F (-4060 °C)
Height	13.31 in (338 mm)
Width	12.17 in (309 mm)
Depth	10.04 in (255 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	41.89 lb(US) (19 kg)

# Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	112
Gtin	3606485242637
Returnability	No
Country Of Origin	CZ

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.99 in (33 cm)
Package 1 Width	14.57 in (37 cm)
Package 1 Length	17.32 in (44 cm)
Package 1 Weight	44.31 lb(US) (20.1 kg)

## **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov