# Product data sheet

Specification





# TeSys F contactor - 4P (4 NO) - AC-1 - <= 440 V 250 A - coil 110 V AC

LC1F1504F5

! Discontinued on: Jul 12, 2021

(!) Discontinued

#### Main

Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC
[Uc] Control Circuit Voltage	110 V AC 50 Hz
[le] Rated Operational Current	250 A (at <104 °F (40 °C)) at <= 440 V AC-1

#### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	250 A (at 104 °F (40 °C))
Rated Breaking Capacity	1200 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand	1200 A 104 °F (40 °C) - 10 s
Current	700 A 104 °F (40 °C) - 30 s
	600 A 104 °F (40 °C) - 1 min
	450 A 104 °F (40 °C) - 3 min
	350 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	160 A aM at <= 440 V
	250 A gG at <= 440 V
Average Impedance	0.35 mOhm - Ith 250 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1
	1500 V VDE 0110 group C
Power Dissipation Per Pole	22 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	4 NO
Control Circuit Voltage Limits	Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C))
	Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In Va	550 VA, 50 Hz 0.3 68 °F (20 °C))
Hold-In Power Consumption In Va	45 VA, 50 Hz 0.3 68 °F (20 °C))

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

2400 cyc/h 131 °F (55 °C)  2335 ms closing 515 ms opening
· ·
· ·
Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end
Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without cable end
Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end
Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end
Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid without cable end
Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end
Power circuit bar 2 25 x 3 mm
Power circuit lugs-ring terminals 1 0.19 in² (120 mm²)
Power circuit connector 1 0.19 in <sup>2</sup> (120 mm <sup>2</sup> )
Power circuit bolted connection
Control circuit 10.62 lbf.in (1.2 N.m)
Power circuit 159.31 lbf.in (18 N.m)
Plate
1216 W
IEC 60947-1
JIS C8201-4-1
EN 60947-4-1
IEC 60947-4-1
EN 60947-1
LROS (Lloyds register of shipping)
UL
RMRoS
CCC
ABS
BV
DNV
RINA
CB
LC1F

#### **Environment**

Ip Degree Of Protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106	
Protective Treatment	тн	
Ambient Air Temperature For Operation	-40140 °F (-4060 °C)	
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)	
Permissible Ambient Air Temperature Around The Device	140158 °F (6070 °C) at Uc	
Height	6.69 in (170 mm)	
Width	7.89 in (200.5 mm)	
Depth	6.73 in (171 mm)	
Operating Altitude	9842.52 ft (3000 m) without derating	
Net Weight	8.44 lb(US) (3.83 kg)	

# Ordering and shipping details

Category 22336-CTR,F-LINE,AC,OPEN,NONREV

Discount Schedule	l12	
Gtin	3389110860641	
Returnability	No	
Country Of Origin	C7	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

## **Contractual warranty**

Warranty 18 months

### Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov