Product data sheet

Specifications





TeSys F contactor - 4P (4 NO) - AC-1 - <= 440 V 250 A - coil 110 V DC

LC1F1504FD

! Discontinued on: Sep 19, 2022

① Discontinued

Main

Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC
[Uc] Control Circuit Voltage	110 V DC
[le] Rated Operational Current	250 A (at <104 °F (40 °C)) at <= 440 V AC-1

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	250 A (at 104 °F (40 °C))
Rated Breaking Capacity	1200 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1200 A 104 °F (40 °C) - 10 s 700 A 104 °F (40 °C) - 30 s 600 A 104 °F (40 °C) - 1 min 450 A 104 °F (40 °C) - 3 min 350 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	160 A aM at <= 440 V 250 A gG at <= 440 V
Average Impedance	0.35 mOhm - Ith 250 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	22 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	4 NO
Control Circuit Voltage Limits	Operational 0.851.1 Uc 131 °F (55 °C)) Drop-out 0.150.2 Uc 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In W	560 W 68 °F (20 °C))
Hold-In Power Consumption In W	4.5 W 68 °F (20 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)
Operating Time	3040 ms closing 3050 ms opening
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid without cable end
	Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end
	Power circuit bar 2 25 x 3 mm
	Power circuit lugs-ring terminals 1 0.19 in ² (120 mm ²)
	Power circuit connector 1 0.19 in ² (120 mm ²)
	Power circuit bolted connection
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m)
	Power circuit 159.31 lbf.in (18 N.m)
Mounting Support	Plate
Heat Dissipation	4.5 W
Standards	EN 60947-1
	JIS C8201-4-1
	IEC 60947-1
	EN 60947-4-1 IEC 60947-4-1
Product Certifications	ABS
	CCC
	CB
	UL
	RMRoS
	BV
	DNV
	LROS (Lloyds register of shipping)
	RINA
	LC1F
Compatibility Code	20.1

Environment

Ip Degree Of Protection	IP2X front face with shrouds IEC 60529	
	IP2X front face with shrouds VDE 0106	
Protective Treatment	тн	
Ambient Air Temperature For Operation	-40140 °F (-4060 °C)	
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)	
Permissible Ambient Air Temperature Around The Device	140158 °F (6070 °C) at Uc	
Height	6.69 in (170 mm)	
Width	7.89 in (200.5 mm)	
Depth	6.73 in (171 mm)	
Operating Altitude	9842.52 ft (3000 m) without derating	
Net Weight	8.44 lb(US) (3.83 kg)	

Ordering and shipping details

Category 22331-CTR,F-LINE,DC,OPEN,NONREV

Discount Schedule	l12
Gtin	3389118093966
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information