Product data sheet

Specifications





() Discontinued

TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 250 A - coil 24 V AC

LC1F150B5

(Discontinued on: Jun 15, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-1 AC-3 AC-4	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	24 V AC 50 Hz	
[Ie] Rated Operational Current	250 A (at <104 °F (40 °C)) at <= 440 V AC-1 150 A (at <131 °F (55 °C)) at <= 440 V AC-3	

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 KV
[Ith] Conventional Free Air Thermal Current	250 A (at 104 °F (40 °C))
Rated Breaking Capacity	1200 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1200 A 104 °F (40 °C) - 10 s 700 A 104 °F (40 °C) - 30 s 600 A 104 °F (40 °C) - 1 min 450 A 104 °F (40 °C) - 3 min 350 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	160 A aM at <= 440 V 250 A gG at <= 440 V
Average Impedance	0.35 mOhm - Ith 250 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	22 W AC-1 8 W AC-3
Overvoltage Category	III
Power Pole Contact Composition	3 NO

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Control Circuit Type	AC 50 Hz
Compatibility Code	LC1F
	UKCA
	ABS CB
	DNV
	LROS (Lloyds register of shipping)
	RINA RMRoS
	UL
	BV
Product Certifications	CCC
	JIS C8201-4-1
	EN 60947-1
	IEC 60947-1 IEC 60947-4-1
Standards	EN 60947-4-1
· · · · · · · · · · · · · · · · · · ·	
Heat Dissipation	1216 W
Mounting Support	Plate
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) Power circuit 159.31 lbf.in (18 N.m)
	Power circuit connector 1 0.19 in ² (120 mm ²) Power circuit bolted connection
	Power circuit lugs-ring terminals 1 0.19 in ² (120 mm ²)
	Power circuit bar 2 25 x 3 mm
	end
	end Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)solid without cable
	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)solid without cable
	end
	end Control circuit screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible with cable
	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible with cable
	cable end
	cable end Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)flexible without
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible without
	515 ms opening
Operating Time	2335 ms closing
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)
Hold-In Power Consumption In Va	45 VA, 50 Hz 0.3 68 °F (20 °C))
Inrush Power In Va	550 VA, 50 Hz 0.3 68 °F (20 °C))
Mechanical Durability	10 Mcycles
	Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C))
Control Circuit Voltage Limits	Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C))
	22 kW at 400 V AC 50/60 Hz (AC-4)
	100 kW at 660690 V AC 50/60 Hz (AC-3) 40 kW at 220230 V AC 50/60 Hz (AC-3)
	90 kW at 500 V AC 50/60 Hz (AC-3)
	80 kW at 440 V AC 50/60 Hz (AC-3)
	80 kW at 415 V AC 50/60 Hz (AC-3)

Environment

Ip Degree Of Protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	-40140 °F (-4060 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)

Permissible Ambient Air Temperature Around The Device	140…158 °F (60…70 °C) at Uc
Height	6.69 in (170 mm)
Width	6.44 in (163.5 mm)
Depth	6.73 in (171 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	7.56 lb(US) (3.43 kg)

Ordering and shipping details

Category	US10I1222336
Discount Schedule	0112
Gtin	3389110226621
Returnability	No
Country Of Origin	CZ

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.27 in (21.0 cm)
Package 1 Width	7.87 in (20.0 cm)
Package 1 Length	9.45 in (24.0 cm)
Package 1 Weight	9.24 lb(US) (4.19 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration