# Product data sheet

Specifications





() Discontinued

### TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 250 A - coil 110 V AC

LC1F150F6

Discontinued on: Jul 12, 2021

Main	
Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Motor control Resistive load
Utilisation Category	AC-1 AC-3
Poles Description	3P
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC
[Uc] Control Circuit Voltage	110 V AC 60 Hz
[le] Rated Operational Current	250 A (at <104 °F (40 °C)) at <= 440 V AC-1 150 A (at <131 °F (55 °C)) at <= 440 V AC-3

#### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	250 A (at 104 °F (40 °C))
Rated Breaking Capacity	1200 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1200 A 104 °F (40 °C) - 10 s 700 A 104 °F (40 °C) - 30 s 600 A 104 °F (40 °C) - 1 min 450 A 104 °F (40 °C) - 3 min 350 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	160 A aM at <= 440 V 250 A gG at <= 440 V
Average Impedance	0.35 mOhm - Ith 250 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	22 W AC-1 8 W AC-3
Overvoltage Category	111
Power Pole Contact Composition	3 NO

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

75 kW at 380400 V AC 50/60 Hz (AC-3)
80 kW at 415 V AC 50/60 Hz (AC-3)
80 kW at 440 V AC 50/60 Hz (AC-3)
90 kW at 500 V AC 50/60 Hz (AC-3)
100 kW at 660690 V AC 50/60 Hz (AC-3)
40 kW at 220230 V AC 50/60 Hz (AC-3)
22 kW at 400 V AC 50/60 Hz (AC-4)
Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C))
Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C))
10 Mcycles
660 VA, 60 Hz 0.3 68 °F (20 °C))
55 VA, 60 Hz 0.3 68 °F (20 °C))
2400 cyc/h 131 °F (55 °C)
2335 ms closing
515 ms opening
Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without
cable end
Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without cable end
Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable
end
Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> )flexible with cable
end Control circuit corow clamp terminals $1,0,00,0,0,01$ in <sup>2</sup> (1, 4 mm <sup>2</sup> ) solid without coble
Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid without cable end
Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid without cable
end
Power circuit bar 2 25 x 3 mm
Power circuit lugs-ring terminals 1 0.19 in <sup>2</sup> (120 mm <sup>2</sup> )
Power circuit connector 1 0.19 in <sup>2</sup> (120 mm <sup>2</sup> )
Control circuit 10.62 lbf.in (1.2 N.m)
Power circuit 159.31 lbf.in (18 N.m)
Plate
1216 W
JIS C8201-4-1
IEC 60947-4-1
EN 60947-1
IEC 60947-1
EN 60947-4-1
СВ
ABS
LROS (Lloyds register of shipping)
BV
CCC
DNV
UL RINA RMRoS
RINA
RINA RMRoS

### Environment

Ip Degree Of Protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	-40140 °F (-4060 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	140158 °F (6070 °C) at Uc

Height	6.69 in (170 mm)	
Width	6.44 in (163.5 mm)	
Depth	6.73 in (171 mm)	
Operating Altitude	9842.52 ft (3000 m) without derating	
Net Weight	7.56 lb(US) (3.43 kg)	

# Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV	
Discount Schedule	112	
Gtin	3389110459883	
Returnability	No	
Country Of Origin	CZ	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.27 in (21 cm)
Package 1 Width	7.87 in (20 cm)
Package 1 Length	9.45 in (24 cm)
Package 1 Weight	9.24 lb(US) (4.19 kg)

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov