Product data sheet

Specification





TeSys F contactor - 3P (3 NO) - AC-3 - <= 440 V 250 A - coil 200...208 V AC

LC1F150L6

! Discontinued on: Jul 12, 2021



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Range | TeSys |
|--------------------------------|--|
| Range Of Product | TeSys F |
| Product Or Component Type | Contactor |
| Device Short Name | LC1F |
| Contactor Application | Resistive load Motor control |
| Utilisation Category | AC-4 AC-1 AC-3 |
| Poles Description | 3P |
| [Ue] Rated Operational Voltage | <= 690 V AC 50/60 Hz <= 460 V DC |
| [Uc] Control Circuit Voltage | 200208 V AC 60 Hz |
| [le] Rated Operational Current | 250 A (at <104 °F (40 °C)) at <= 440 V AC-1 150 A (at <131 °F (55 °C)) at <= 440 V AC-3 |

Complementary

| [Uimp] Rated Impulse Withstand Voltage | 8 kV |
|--|--|
| [Ith] Conventional Free Air Thermal Current | 250 A (at 104 °F (40 °C)) |
| Rated Breaking Capacity | 1200 A conforming to IEC 60947-4-1 |
| [Icw] Rated Short-Time Withstand Current | 1200 A 104 °F (40 °C) - 10 s 700 A 104 °F (40 °C) - 30 s 600 A 104 °F (40 °C) - 1 min 450 A 104 °F (40 °C) - 3 min 350 A 104 °F (40 °C) - 10 min |
| Associated Fuse Rating | 160 A aM at <= 440 V 250 A gG at <= 440 V |
| Average Impedance | 0.35 mOhm - Ith 250 A 50 Hz |
| [Ui] Rated Insulation Voltage | 1000 V IEC 60947-4-1 1500 V VDE 0110 group C |
| Power Dissipation Per Pole | 22 W AC-1 8 W AC-3 |
| Overvoltage Category | III |
| Power Pole Contact Composition | 3 NO |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Motor Power Kw | 75 kW at 380400 V AC 50/60 Hz (AC-3) 80 kW at 415 V AC 50/60 Hz (AC-3) 80 kW at 440 V AC 50/60 Hz (AC-3) 90 kW at 500 V AC 50/60 Hz (AC-3) 100 kW at 660690 V AC 50/60 Hz (AC-3) 40 kW at 220230 V AC 50/60 Hz (AC-3) 22 kW at 400 V AC 50/60 Hz (AC-4) |
|--|--|
| Control Circuit Voltage Limits | Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C)) Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C)) |
| Mechanical Durability | 10 Mcycles |
| Inrush Power In Va | 660 VA, 60 Hz 0.3 68 °F (20 °C)) |
| Hold-In Power Consumption In Va | 55 VA, 60 Hz 0.3 68 °F (20 °C)) |
| Maximum Operating Rate | 2400 cyc/h 131 °F (55 °C) |
| Operating Time | 2335 ms closing 515 ms opening |
| Connections - Terminals | Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without cable end Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid without cable end Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end Power circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end Power circuit bar 2 25 x 3 mm Power circuit lugs-ring terminals 1 0.19 in² (120 mm²) Power circuit connector 1 0.19 in² (120 mm²) Power circuit bolted connection |
| Tightening Torque | Control circuit 10.62 lbf.in (1.2 N.m) Power circuit 159.31 lbf.in (18 N.m) |
| Mounting Support | Plate |
| Heat Dissipation | 1216 W |
| Standards | JIS C8201-4-1 EN 60947-1 EN 60947-4-1 IEC 60947-4-1 |
| Product Certifications | RINA BV ABS UL DNV RMRoS CB LROS (Lloyds register of shipping) CCC |
| Compatibility Code | LC1F |
| Control Circuit Type | AC 60 Hz |
| Environment | |
| Ip Degree Of Protection | IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106 |
| Protective Treatment | тн |
| Ambient Air Temperature For Operation | -40140 °F (-4060 °C) |
| Ambient Air Temperature For Storage | -76176 °F (-6080 °C) |
| Permissible Ambient Air Temperature Around The Device | 140158 °F (6070 °C) at Uc |

| Height | 6.69 in (170 mm) |
|--------------------|--------------------------------------|
| Width | 6.44 in (163.5 mm) |
| Depth | 6.73 in (171 mm) |
| Operating Altitude | 9842.52 ft (3000 m) without derating |
| Net Weight | 7.56 lb(US) (3.43 kg) |

Ordering and shipping details

| Category | US10I1222336 |
|-------------------|---------------|
| Discount Schedule | 0112 |
| Gtin | 3389110226669 |
| Returnability | No |
| Country Of Origin | US |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 8.27 in (21 cm) |
| Package 1 Width | 7.87 in (20 cm) |
| Package 1 Length | 9.45 in (24 cm) |
| Package 1 Weight | 9.24 lb(US) (4.19 kg) |

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Eu Rohs Directive | Compliant |
|---------------------------|---|
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |