Product data sheet

Specifications





() Discontinued

TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 275 A - coil 220 V AC

LC1F185M6

() Discontinued on: Feb 17, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Motor control Resistive load
Utilisation Category	AC-3 AC-4 AC-1
Poles Description	3P
[Ue] Rated Operational Voltage	<= 460 V DC <= 690 V AC 50/60 Hz
[Uc] Control Circuit Voltage	220 V AC 60 Hz
[Ie] Rated Operational Current	275 A (at <104 °F (40 °C)) at <= 440 V AC-1 185 A (at <131 °F (55 °C)) at <= 440 V AC-3

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 KV
[Ith] Conventional Free Air Thermal Current	275 A (at 104 °F (40 °C))
Rated Breaking Capacity	1480 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1500 A 104 °F (40 °C) - 10 s 920 A 104 °F (40 °C) - 30 s 740 A 104 °F (40 °C) - 1 min 500 A 104 °F (40 °C) - 3 min 400 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	200 A aM at <= 440 V 315 A gG at <= 440 V
Average Impedance	0.33 mOhm - Ith 275 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	12 W AC-3 25 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	3 NO

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

90 kW at 380400 V AC 50/60 Hz (AC-3)
100 kW at 415 V AC 50/60 Hz (AC-3)
100 kW at 440 V AC 50/60 Hz (AC-3)
110 kW at 500 V AC 50/60 Hz (AC-3)
110 kW at 660690 V AC 50/60 Hz (AC-3)
55 kW at 220230 V AC 50/60 Hz (AC-3)
33 kW at 400 V AC 50/60 Hz (AC-4)
Operational 0.851.1 Uc 50/60 Hz 131 °F (55 °C))
Drop-out 0.350.55 Uc 50/60 Hz 131 °F (55 °C))
10 Mcycles
970 VA, 60 Hz 0.3 68 °F (20 °C))
66 VA, 60 Hz 0.3 68 °F (20 °C))
2400 cyc/h 131 °F (55 °C)
2035 ms closing
715 ms opening
Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible without
cable end Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)flexible without
cable end
Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible with cable
end
Control circuit screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible with cable
end
Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)solid without cable
end
Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)solid without cable
end
Power circuit bar 2 25 x 3 mm
Power circuit lugs-ring terminals 1 0.23 in ² (150 mm ²)
Power circuit connector 1 0.23 in ² (150 mm ²)
Power circuit bolted connection
Control circuit 10.62 lbf.in (1.2 N.m)
Power circuit 159.31 lbf.in (18 N.m)
Plate
Plate 1824 W
1824 W
1824 W JIS C8201-4-1 IEC 60947-4-1
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1
1824 W JIS C8201-4-1 IEC 60947-4-1
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-4-1 IEC 60947-1
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 IEC 60947-1 UL
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-4-1 IEC 60947-1
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 IEC 60947-4-1 IEC 60947-1
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-4-1 IEC 60947-1 UL DNV BV
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 EN 60947-4-1 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping)
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 IEC 60947-4-1 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping) ABS
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 IEC 60947-4-1 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping) ABS RMRoS
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-4 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping) ABS RMRoS RINA
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 IEC 60947-4-1 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping) ABS RMRoS
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-4-1 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping) ABS RMRoS RINA CB CCC
1824 W JIS C8201-4-1 IEC 60947-4-1 EN 60947-4-1 IEC 60947-4-1 IEC 60947-1 UL DNV BV LROS (Lloyds register of shipping) ABS RMRoS RINA CB

Environment

Ip Degree Of Protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	23131 °F (-555 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	-40158 °F (-4070 °C)

Height	6.85 in (174 mm)	
Width	6.63 in (168.5 mm)	
Depth	7.13 in (181 mm)	
Operating Altitude	9842.52 ft (3000 m) without derating	
Net Weight	10.25 lb(US) (4.65 kg)	

Ordering and shipping details

Category	US10I1222336	
Discount Schedule	0112	
Gtin	3389110226775	
Returnability	No	
Country Of Origin	US	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.66 in (22 cm)
Package 1 Width	7.87 in (20 cm)
Package 1 Length	9.45 in (24 cm)
Package 1 Weight	11.22 lb(US) (5.09 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov