Product data sheet

Specifications





TeSys F contactor - 4P (4 NO) -AC-1 - <= 440 V 315 A - coil 110 V DC

LC1F2254FD

(!) To be discontinued on: Jun 30, 2024

① Discontinued

Main

Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	<= 460 V DC <= 690 V AC 50/60 Hz
[Uc] Control Circuit Voltage	110 V DC
[le] Rated Operational Current	315 A (at <104 °F (40 °C)) at <= 440 V AC-1

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 KV
[Ith] Conventional Free Air Thermal Current	315 A (at 104 °F (40 °C))
Rated Breaking Capacity	1800 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1800 A 104 °F (40 °C) - 10 s 1000 A 104 °F (40 °C) - 30 s 850 A 104 °F (40 °C) - 1 min 560 A 104 °F (40 °C) - 3 min 440 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	315 A gG at <= 440 V 250 A aM at <= 440 V
Average Impedance	0.32 mOhm - Ith 315 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	32 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	4 NO
Control Circuit Voltage Limits	Operational 0.851.1 Uc 131 °F (55 °C)) Drop-out 0.150.2 Uc 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In W	800 W 68 °F (20 °C))
Hold-In Power Consumption In W	5 W 68 °F (20 °C)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)	
Operating Time	3040 ms closing 3050 ms opening	
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible without	
	cable end Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)flexible without cable end	
	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible with cable end	
	Control circuit screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible with cable end	
	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)solid without cable end	
	Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)solid without cable end	
	Power circuit bar 2 32 x 4 mm	
	Power circuit lugs-ring terminals 1 0.29 in ² (185 mm ²)	
	Power circuit connector 1 0.29 in ² (185 mm ²)	
	Power circuit bolted connection	
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m)	
	Power circuit 309.78 lbf.in (35 N.m)	
Mounting Support	Plate	
Heat Dissipation	5 W	
Standards	IEC 60947-4-1	
	IEC 60947-1	
	JIS C8201-4-1	
	EN 60947-1	
	EN 60947-4-1	
Product Certifications	DNV	
	RINA	
	ABS	
	RMRoS	
	CCC	
	CB	
	BV	
	LROS (Lloyds register of shipping)	
	UL	
	UKCA	
Compatibility Code	LC1F	
Control Circuit Type	DC standard	

Environment

Ip Degree Of Protection	IP20 front face with shrouds IEC 60529 IP20 front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	23131 °F (-555 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	-40158 °F (-4070 °C)
Height	7.76 in (197 mm)
Width	8.21 in (208.5 mm)
Depth	7.13 in (181 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	12.24 lb(US) (5.55 kg)

Ordering and shipping details

Category

22336-CTR,F-LINE,AC,OPEN,NONREV

Discount Schedule	112
Gtin	3389118095687
Returnability	No

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.46 in (21.5 cm)
Package 1 Width	9.25 in (23.5 cm)
Package 1 Length	10.43 in (26.5 cm)
Package 1 Weight	14.11 lb(US) (6.4 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information