# Product data sheet

Specifications





### TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 630 A - coil 110 V AC

LC1F630G7

Discontinued on: Jun 15, 2023

① Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-1 AC-4 AC-3	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 1000 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	120 V AC 40400 Hz	
[Ie] Rated Operational Current	1000 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 630 A (at <131 °F (55 °C)) at <= 440 V AC AC-3	

### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	1000 A (at 104 °F (40 °C)) 1250 A
Rated Breaking Capacity	5040 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	5050 A 104 °F (40 °C) - 10 s 4400 A 104 °F (40 °C) - 30 s 3400 A 104 °F (40 °C) - 1 min 2200 A 104 °F (40 °C) - 3 min 1600 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	1000 A gG at <= 440 V 630 A aM at <= 440 V
Average Impedance	0.12 mOhm - Ith 1000 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	120 W AC-1 48 W AC-3
Overvoltage Category	III

Power Pole Contact Composition 3 NO

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Motor Power Kw	335 kW at 380400 V AC 50/60 Hz (AC-3)
	375 kW at 415 V AC 50/60 Hz (AC-3)
	400 kW at 440 V AC 50/60 Hz (AC-3)
	400 kW at 500 V AC 50/60 Hz (AC-3)
	450 kW at 660690 V AC 50/60 Hz (AC-3)
	450 kW at 1000 V AC 50/60 Hz (AC-3)
	200 kW at 220230 V AC 50/60 Hz (AC-3)
	100 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Voltage Limits	Operational 0.851.1 Uc 40400 Hz 131 °F (55 °C))
gg	Drop-out 0.250.5 Uc 40400 Hz 131 °F (55 °C))
Mechanical Durability	5 Mcycles
Inrush Power In Va	1650 VA, 40400 Hz 0.9 68 °F (20 °C))
Hold-In Power Consumption In Va	22 VA, 40400 Hz 0.9 68 °F (20 °C))
Maximum Operating Rate	1200 cyc/h 131 °F (55 °C)
Operating Time	4080 ms closing
	100200 ms opening
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without
	cable end Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without
	cable end
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible with cable
	end
	Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> )flexible with cable
	end
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid without cable
	end
	Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid without cable
	end
	Power circuit bar 2 60 x 5 mm
	Power circuit bolted connection
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m)
	Power circuit 513.34 lbf.in (58 N.m)
Mounting Support	Plate
Heat Dissipation	20 W
Standards	JIS C8201-4-1
Stanuarus	IEC 60947-4-1
	IEC 60947-1
	EV 60947-1 EN 60947-4-1
	EN 60947-1
	EN 00347-1
Product Certifications	LROS (Lloyds register of shipping)
	RINA
	CCC
	BV
	ABS
	UL
	DNV
	CB
	RMRoS
	UKCA
Compatibility Code	LC1F
	2011
Control Circuit Type	AC 40400 Hz

### Environment

Ip Degree Of Protection	IP20 front face with shrouds IEC 60529 IP20 front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	23131 °F (-555 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	-40158 °F (-4070 °C)

Height	11.97 in (304 mm)
Width	12.17 in (309 mm)
Depth	10.04 in (255 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	41.01 lb(US) (18.6 kg)

# Ordering and shipping details

Category	US10I1222336
Discount Schedule	0112
Gtin	3389110227147
Returnability	No
Country Of Origin	CZ

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.02 in (28.0 cm)
Package 1 Width	11.02 in (28.0 cm)
Package 1 Length	13.78 in (35.0 cm)
Package 1 Weight	41.23 lb(US) (18.7 kg)

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

### **Certifications & Standards**

California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration