## Product data sheet

Specification





TeSys

Contactor

# Contactor, TeSys K, 3P, AC-3, It or eq to 440V 6A, 1 NC aux., 24VAC coil

LC1K06015B7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 57.00 USD

## Main Range

**Product Or Component Type** 

[Ith] Conventional Free Air

Irms Rated Making Capacity

**Thermal Current** 

| Device Short Name                      | LC1K  |
|--|---|
| Device Application                     | Control   |
| Contactor Application                  | Motor control   |
| Complementary                          |   |
| Utilisation Category                   | AC-3  |
|  | AC-3e   |
|  | AC-4  |
| Poles Description                      | 3P  |
| Power Pole Contact Composition         | 3 NO  |
| [Ue] Rated Operational Voltage         | Power circuit <= 690 V AC <= 400 Hz                             |
|  | Signalling circuit <= 690 V AC <= 400 Hz                        |
| [le] Rated Operational Current         | 6 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit  |
|  | 6 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit |
| Control Circuit Type                   | AC 50/60 Hz   |
| [Uc] Control Circuit Voltage           | 24 V AC 50/60 Hz  |
| Motor Power Kw                         | 1.5 kW 220230 V AC 50/60 Hz AC-3                                |
|  | 2.2 kW 380415 V AC 50/60 Hz AC-3                                |
|  | 3 kW 440/690 V AC 50/60 Hz AC-3                                 |
|  | 1.5 kW 220230 V AC 50/60 Hz AC-3e                               |
|  | 2.2 kW 380415 V AC 50/60 Hz AC-3e                               |
|  | 3 kW 440/690 V AC 50/60 Hz AC-3e                                |
|  | 1.5 kW 220230 V AC 50/60 Hz AC-4                                |
|  | 2.2 kW 380415 V AC 50/60 Hz AC-4                                |
|  | 3 kW 440/690 V AC 50/60 Hz AC-4                                 |
| Auxiliary Contact Composition          | 1 NC  |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV  |
| Overvoltage Category                   | III   |
|  |   |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

20 A (at 140 °F (60 °C)) for power circuit

10 A (at 122 °F (50 °C)) for signalling circuit

110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947

| Rated Breaking Capacity                  | 110 A at 220230 V conforming to IEC 60947<br>110 A at 380400 V conforming to IEC 60947<br>110 A at 415 V conforming to IEC 60947<br>110 A at 440 V conforming to IEC 60947<br>80 A at 500 V conforming to IEC 60947<br>70 A at 660690 V conforming to IEC 60947   |
|--|---|
| [Icw] Rated Short-Time Withstand Current | 90 A 122 °F (50 °C) - 1 s for power circuit  85 A 122 °F (50 °C) - 5 s for power circuit  80 A 122 °F (50 °C) - 10 s for power circuit  60 A 122 °F (50 °C) - 30 s for power circuit  45 A 122 °F (50 °C) - 1 min for power circuit  40 A 122 °F (50 °C) - 3 min for power circuit  20 A 122 °F (50 °C) - >= 15 min for power circuit  80 A - 1 s for signalling circuit  90 A - 500 ms for signalling circuit  110 A - 100 ms for signalling circuit   |
| Associated Fuse Rating                   | 25 A gG at <= 440 V for power circuit 25 A aM for power circuit 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660  |
| Average Impedance                        | 3 mOhm - Ith 16 A 50 Hz for power circuit   |
| [Ui] Rated Insulation Voltage            | Power circuit 600 V UL 508 Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-5-1 Signalling circuit 600 V UL 508 Power circuit 600 V CSA C22.2 No 14 Signalling circuit 600 V CSA C22.2 No 14   |
| Insulation Resistance                    | > 10 MOhm for signalling circuit  |
| Inrush Power In Va                       | 30 VA (at 68 °F (20 °C))  |
| Hold-In Power Consumption In Va          | 4.5 VA (at 68 °F (20 °C))   |
| Heat Dissipation                         | 1.3 W   |
| Control Circuit Voltage Limits           | Operational: 0.81.15 Uc (at <122 °F (50 °C))<br>Drop-out: >= 0.20 Uc (at <122 °F (50 °C))   |
| Connections - Terminals                  | solder pins 0.00 in (0.035 mm))   |
| Maximum Operating Rate                   | 3600 cyc/h  |
| Auxiliary Contacts Type                  | Instantaneous 1 NC  |
| Signalling Circuit Frequency             | <= 400 Hz   |
| Minimum Switching Current                | 5 mA for signalling circuit   |
| Minimum Switching Voltage                | 17 V for signalling circuit   |
| Mounting Support                         | Printed circuit boards  |
| Operating Time                           | 1020 ms coil de-energisation and NO opening<br>1020 ms coil energisation and NO closing   |
| Safety Reliability Level                 | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1  |
| Non Overlap Distance                     | 0.02 in (0.5 mm)  |
| Mechanical Durability                    | 10 Mcycles  |
| Electrical Durability                    | 1.3 Mcycles 6 A AC-3 <= 440 V<br>1.3 Mcycles 6 A AC-3e <= 440 V<br>0.05 Mcycles 36 A AC-4 <= 440 V  |
| Mechanical Robustness                    | Shocks contactor closed, on X axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Y axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Z axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on X axis6 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Y axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6 Vibrations contactor opened2 Gn, 5300 Hz IEC 60068-2-6 |

| Height     | 2.28 in (58 mm)       |
|------------|-----------------------|
| Width      | 1.77 in (45 mm)       |
| Depth      | 2.24 in (57 mm)       |
| Net Weight | 0.40 lb(US) (0.18 kg) |

#### **Environment**

| Environment                         |  |
|-------------------------------------|--|
| Standards                           | EN/IEC 60947-4-1<br>GB/T 14048.4<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1<br>JIS C8201-4-1            |
| Product Certifications              | CB Scheme CCC UL CSA EAC CE  |
| Ip Degree Of Protection             | IP2X VDE 0106  |
| Protective Treatment                | TC IEC 60068<br>TC DIN 50016   |
| Ambient Air Temperature For Storage | -58176 °F (-5080 °C)   |
| Operating Altitude                  | 6561.68 ft (2000 m) without derating   |
| Flame Retardance                    | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |

# Ordering and shipping details

| Category          | US10I1222326  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| Gtin              | 3389110488159 |
| Returnability     | No            |
| Country Of Origin | ID            |

## **Packing Units**

| •                            |                          |
|------------------------------|--------------------------|
| Unit Type Of Package 1       | PCE                      |
| Number Of Units In Package 1 | 1                        |
| Package 1 Height             | 1.89 in (4.8 cm)         |
| Package 1 Width              | 2.44 in (6.2 cm)         |
| Package 1 Length             | 2.68 in (6.8 cm)         |
| Package 1 Weight             | 7.13 oz (202.0 g)        |
| Unit Type Of Package 2       | S02                      |
| Number Of Units In Package 2 | 50                       |
| Package 2 Height             | 5.91 in (15 cm)          |
| Package 2 Width              | 11.81 in (30 cm)         |
| Package 2 Length             | 15.75 in (40 cm)         |
| Package 2 Weight             | 23.08 lb(US) (10.468 kg) |

## **Contractual warranty**

Warranty

18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>Ø</b> | Toxic Heavy Metal Free     |     |
| <b>Ø</b> | Mercury Free               |     |
| <b>9</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant   |
|                           | EU RoHS Declaration   |
| China Rohs Regulation     | China RoHS declaration  |
|                           | Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
|                           |   |