# Product data sheet

Specifications



### TeSys Deca reversing contactor -3P(3 NO) - AC-3 - <= 440 V 25 A -24 V AC coil

LC2D253B7

() Discontinued on: Oct 8, 2021

(!) Discontinued

#### Main

Range	TeSys
Product Name	TeSys Deca
Product Or Component Type	Reversing contactor
Device Short Name	LC2D
Contactor Application	Resistive load Motor control
Utilisation Category	AC-1 AC-3
Device Presentation	Preassembled with reversing power busbar
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[le] Rated Operational Current	25 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 25 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit
Motor Power Kw	5.5 kW at 220230 V AC 50 Hz 11 kW at 380400 V AC 50 Hz 11 kW at 415440 V AC 50 Hz 15 kW at 500 V AC 50 Hz 15 kW at 660690 V AC 50 Hz
Motor Power Hp (Ul / Csa)	3 hp at 230/240 V AC 60 Hz for 1 phase motors 5 hp at 200/208 V AC 60 Hz for 3 phase motors 2 hp at 115 V AC 60 Hz for 1 phase motors 7.5 hp at 230/240 V AC 60 Hz for 3 phase motors 15 hp at 460/480 V AC 60 Hz for 3 phase motors 20 hp at 575/600 V AC 60 Hz for 3 phase motors
Control Circuit Type	AC 50/60 Hz
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz
Auxiliary Contact Composition	1 NO + 1 NC
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C)) for signalling circuit 25 A (at 140 °F (60 °C)) for power circuit
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 450 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	450 A at 440 V for power circuit conforming to IEC 60947

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Life Is On Schneider

[Icw] Rated Short-Time Withstand	50 A 104 °F (40 °C) - 10 min for power circuit
Current	120 A 104 °F (40 °C) - 1 min for power circuit
	240 A 104 °F (40 °C) - 10 s for power circuit
	$380 \text{ A } 104 ^{\circ}\text{F} (40 ^{\circ}\text{C}) - 1 \text{ s for power circuit}$
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
C C	63 A gG at <= 690 V coordination type 1 for power circuit
	40 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2 mOhm - Ith 25 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1
	Power circuit 600 V CSA
	Power circuit 600 V UL
	Signalling circuit 690 V IEC 60947-1
	Signalling circuit 600 V CSA
	Signalling circuit 600 V UL
Electrical Durability	
Electrical Durability	1.65 Mcycles 25 A AC-3 <= 440 V
	1.4 Mcycles 40 A AC-1 <= 440 V
Power Dissipation Per Pole	1.25 W AC-3
• • • • • • • • • • • • • • • • • • • •	3.2 W AC-1
Front Cover	With
Interlocking Type	Mechanical
Mounting Support	Rail
3	Plate
Standards	CSA C22.2 No 14
oundardo	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1
	IEC 60947-5-1 UL 508
Product Certifications	RINA
	CSA
	UL
	DNV
	BV
	CCC
	LROS (Lloyds register of shipping)
	GL
	GOST
Connections - Terminals	Control circuit opring terminals 1,0,00 in2/2,5 mm2/flouible without ophile and
	Control circuit spring terminals 1 0.00 in <sup>2</sup> (2.5 mm <sup>2</sup> )flexible without cable end
	Control circuit spring terminals 2 0.00 in <sup>2</sup> (2.5 mm <sup>2</sup> )flexible without cable end
	Power circuit spring terminals 1 0.01 in <sup>2</sup> (4 mm <sup>2</sup> )flexible without cable end
	Power circuit spring terminals 2 0.01 in <sup>2</sup> (4 mm <sup>2</sup> )flexible without cable end
Operating Time	1222 ms closing
	419 ms opening
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Maximum Operating Pata	2600 mm/h 110 °F (60 °C)
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

### Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz
Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))

Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))	
Heat Dissipation	23 W 50/60 Hz	
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1	
Signalling Circuit Frequency	25400 Hz	
Minimum Switching Current	5 mA for signalling circuit	
Minimum Switching Voltage	17 V for signalling circuit	
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Insulation Resistance	> 10 MOhm for signalling circuit	

#### Environment

Ip Degree Of ProtectionIP20 front face IEC 60529Climatic WithstandIACS E10 IEC 60947-1 Annex Q category DProtective TreatmentTH IEC 60068-2-30Pollution Degree3Ambient Air Temperature For Operation-40140 °F (-4060 °C) 140158 °F (6070 °C) with deratingAmbient Air Temperature For Operation-40176 °F (-6080 °C)Operating Altitude09842.52 ft (03000 m)Fire Resistance1562 °F (850 °C) IEC 60695-2-1Flame RetardanceV1 conforming to UL 94Mechanical RobustnessVibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 msHeight3.90 in (99 mm)Width3.54 in (90 mm)Depth3.54 in (90 mm)		
IEC 60947-1 Annex Q category D         Protective Treatment       TH IEC 60068-2-30         Pollution Degree       3         Ambient Air Temperature For Operation       -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating         Ambient Air Temperature For Storage       -76176 °F (-6080 °C)         Operating Altitude       09842.52 ft (03000 m)         Fire Resistance       1562 °F (850 °C) IEC 60695-2-1         Flame Retardance       V1 conforming to UL 94         Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz         Vibrations contactor open8 Gn for 11 ms Shocks contactor open8 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)	ree Of Protection IP20 fi	ont face IEC 60529
Pollution Degree       3         Ambient Air Temperature For Operation       -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating         Ambient Air Temperature For Storage       -76176 °F (-6080 °C)         Operating Altitude       09842.52 ft (03000 m)         Fire Resistance       1562 °F (850 °C) IEC 60695-2-1         Flame Retardance       V1 conforming to UL 94         Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed15 Gn for 11 ms Shocks contactor closed15 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)	1,001	
Ambient Air Temperature For Operation       -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating         Ambient Air Temperature For Storage       -76176 °F (-6080 °C)         Operating Altitude       09842.52 ft (03000 m)         Fire Resistance       1562 °F (850 °C) IEC 60695-2-1         Flame Retardance       V1 conforming to UL 94         Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz         Vibrations contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)	tive Treatment TH IEC	\$ 60068-2-30
Operation       140158 °F (6070 °C) with derating         Ambient Air Temperature For Storage       -76176 °F (-6080 °C)         Operating Altitude       09842.52 ft (03000 m)         Fire Resistance       1562 °F (850 °C) IEC 60695-2-1         Flame Retardance       V1 conforming to UL 94         Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz         Shocks contactor open8 Gn for 11 ms         Shocks contactor open8 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)	on Degree 3	
Storage     Operating Altitude     09842.52 ft (03000 m)       Fire Resistance     1562 °F (850 °C) IEC 60695-2-1       Flame Retardance     V1 conforming to UL 94       Mechanical Robustness     Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms       Height     3.90 in (99 mm)       Width     3.54 in (90 mm)		
Fire Resistance       1562 °F (850 °C) IEC 60695-2-1         Flame Retardance       V1 conforming to UL 94         Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz         Vibrations contactor closed4 Gn, 5300 Hz       Shocks contactor closed15 Gn for 11 ms         Shocks contactor open8 Gn for 11 ms       Shocks contactor open8 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)		76 °F (-6080 °C)
Flame Retardance       V1 conforming to UL 94         Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz         Vibrations contactor closed4 Gn, 5300 Hz       Shocks contactor closed15 Gn for 11 ms         Shocks contactor open8 Gn for 11 ms       Shocks contactor open8 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)	ting Altitude 0984	2.52 ft (03000 m)
Mechanical Robustness       Vibrations contactor open2 Gn, 5300 Hz         Vibrations contactor closed4 Gn, 5300 Hz       Shocks contactor closed15 Gn for 11 ms         Shocks contactor open8 Gn for 11 ms       Shocks contactor open8 Gn for 11 ms         Height       3.90 in (99 mm)         Width       3.54 in (90 mm)	esistance 1562 °	F (850 °C) IEC 60695-2-1
Vibrations contactor closed4 Gn, 5300 Hz       Shocks contactor closed15 Gn for 11 ms       Shocks contactor open8 Gn for 11 ms       Height     3.90 in (99 mm)       Width     3.54 in (90 mm)	Retardance V1 cor	forming to UL 94
Width         3.54 in (90 mm)	Vibrati Shock	ons contactor closed4 Gn, 5300 Hz s contactor closed15 Gn for 11 ms
	3.90 ir	(99 mm)
Depth         3.54 in (90 mm)	3.54 ir	(90 mm)
	3.54 ir	(90 mm)
Net Weight         1.74 lb(US) (0.787 kg)	əight 1.74 lt	(US) (0.787 kg)

# Ordering and shipping details

Category	22354-CTR,TESYS D,OPEN,9-38A AC
Discount Schedule	112
Gtin	3389110682694
Returnability	No
Country Of Origin	FR

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.69 in (11.9 cm)
Package 1 Width	4.49 in (11.4 cm)

 Package 1 Length
 4.33 in (11 cm)

 Package 1 Weight
 28.75 oz (815 g)

#### **Contractual warranty**

Warranty

18 months

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes
 Pvc Free

#### **Certifications & Standards**

Compliant
EU RoHS Declaration
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov