# Product data sheet

Specifications





### TeSys Deca reversing contactor -3P(3 NO) - AC-3 - <= 440 V 25 A -48 V DC coil

LC2D25ED

#### ① Discontinued

#### Main

Range	TeSys TeSys Deca					
Product Name	TeSys D TeSys Deca					
Product Or Component Type	Reversing contactor					
Device Short Name	LC2D					
Contactor Application	Resistive load Motor control					
Utilisation Category	AC-1 AC-3 AC-3e					
Device Presentation	Preassembled with reversing power busbar					
Poles Description	3P					
Power Pole Contact Composition	3 NO					
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC					
[le] Rated Operational Current	25 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit					
Motor Power Kw	5.5 kW at 220230 V AC 50-60 Hz 11 kW at 380400 V AC 50-60 Hz 11 kW at 415 V AC 50-60 Hz 11 kW at 440 V AC 50-60 Hz 15 kW at 500 V AC 50-60 Hz 15 kW at 660690 V AC 50-60 Hz					
Motor Power Hp (UI / Csa)	3 hp at 230/240 V AC 60 Hz for 1 phase motors 5 hp at 200/208 V AC 60 Hz for 3 phase motors 2 hp at 115 V AC 60 Hz for 1 phase motors 7.5 hp at 230/240 V AC 60 Hz for 3 phase motors 15 hp at 460/480 V AC 60 Hz for 3 phase motors 20 hp at 575/600 V AC 60 Hz for 3 phase motors					
Control Circuit Type	DC standard					
[Uc] Control Circuit Voltage	48 V DC					
Auxiliary Contact Composition	1 NO + 1 NC					
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947					
Overvoltage Category	III					
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C)) for signalling circuit 40 A (at 140 °F (60 °C)) for power circuit					

Disclaime: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 450 A at 440 V for power circuit conforming to IEC 60947				
Rated Breaking Capacity	450 A at 440 V for power circuit conforming to IEC 60947				
[Icw] Rated Short-Time Withstand Current	50 A 104 °F (40 °C) - 10 min for power circuit 120 A 104 °F (40 °C) - 1 min for power circuit 240 A 104 °F (40 °C) - 10 s for power circuit 380 A 104 °F (40 °C) - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit				
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 40 A gG at <= 690 V coordination type 2 for power circuit				
Average Impedance	2 mOhm - Ith 40 A 50 Hz for power circuit				
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL				
Electrical Durability	1.65 Mcycles 25 A AC-3 <= 440 V 1.4 Mcycles 40 A AC-1 <= 440 V 1.65 Mcycles 25 A AC-3e <= 440 V				
Power Dissipation Per Pole	1.25 W AC-3 3.2 W AC-1 1.25 W AC-3e				
Front Cover	With				
Interlocking Type	Mechanical				
Mounting Support	Plate Rail				
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 IEC 60335-1				
Product Certifications	DNV CSA CCC UL GL LROS (Lloyds register of shipping) BV RINA GOST UKCA CB				

Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without cable end					
	Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without cable end					
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )flexible with cable end					
	Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> )flexible with cable end					
	Control circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid					
	Control circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (14 mm <sup>2</sup> )solid					
	Power circuit screw clamp terminals 1 0.000.02 in <sup>2</sup> (2.510 mm <sup>2</sup> )flexible without cable end					
	Power circuit screw clamp terminals 2 0.000.02 in <sup>2</sup> (2.510 mm <sup>2</sup> )flexible without cable end					
	Power circuit screw clamp terminals 1 0.000.02 in <sup>2</sup> (110 mm <sup>2</sup> )flexible with cable end					
	Power circuit screw clamp terminals 2 0.000.01 in <sup>2</sup> (1.56 mm <sup>2</sup> )flexible with cable end					
	Power circuit screw clamp terminals 1 0.000.02 in <sup>2</sup> (1.510 mm <sup>2</sup> )solid					
	Power circuit screw clamp terminals 2 0.000.02 in <sup>2</sup> (2.510 mm <sup>2</sup> )solid					
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm					
	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2					
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm					
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2 Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2					
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals pozidriv No 2					
Operating Time	53.5572.45 ms closing					
	1624 ms opening					
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1					
	B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1					
Mechanical Durability	30 Mcycles					
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)					

# Complementary

Coil Technology	Built-in bidirectional peak limiting diode suppressor				
Control Circuit Voltage Limits	0.10.25 Uc -40158 °F (-4070 °C) drop-out DC 0.71.25 Uc -40140 °F (-4060 °C) operational DC 11.25 Uc 140158 °F (6070 °C) operational DC				
Time Constant	28 ms				
Inrush Power In W	5.4 W 68 °F (20 °C))				
Hold-In Power Consumption In W	5.4 W 68 °F (20 °C)				
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1				
Signalling Circuit Frequency	25400 Hz				
Minimum Switching Current	5 mA for signalling circuit				
Minimum Switching Voltage	17 V for signalling circuit				
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact				
Insulation Resistance	> 10 MOhm for signalling circuit				

### Environment

Ip Degree Of Protection	IP20 front face IEC 60529		
Climatic Withstand	IACS E10 IEC 60947-1 Annex Q category D		
Protective Treatment	TH IEC 60068-2-30		
Pollution Degree	3		

Ambient Air Temperature For Operation	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating				
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)				
Operating Altitude	09842.52 ft (03000 m)				
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1				
Flame Retardance	V1 conforming to UL 94				
Mechanical Robustness	Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms				
Height	3.35 in (85 mm)				
Width	3.54 in (90 mm)				
Depth	3.98 in (101 mm)				
Net Weight	2.46 lb(US) (1.117 kg)				

#### Ordering and shipping details

Category	22355-CTR,TESYS D,OPEN,9-38A DC				
Discount Schedule	112				
Gtin	3389110392623				
Returnability	No				

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.29 in (10.9 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	4.65 in (11.8 cm)
Package 1 Weight	2.58 lb(US) (1.17 kg)

# **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free


#### **Certifications & Standards**


Reach Regulation	REACh Declaration				
Eu Rohs Directive	Compliant with Exemptions				
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.				
Environmental Disclosure	Product Environmental Profile				
Circularity Profile	End of Life Information				

# Product data sheet

#### **Dimensions Drawings**

#### Dimensions





LC2 or 2 x LC1	а	b	c <sup>(1)</sup>	e1	e2	G
D09 to D18 (AC)	90	77	86	4	1.5	80
D093 to D123 (AC)	90	99	86	-	-	80
D09 to D18 (DC)	90	77	95	4	1.5	80
D093 to D123 (DC)	90	99	95	-	-	80
D25 to D38 (AC)	90	85	92	9	5	80
D183 to D383 (AC)	90	99	92	-	-	80
D25 to D32 (DC)	90	85	101	9	5	80
D183 to D383 (DC)	90	99	101	-	-	80
e1 and e2: including cabling.						
(1) With safety cover, without add-on block.						

### Product data sheet

Connections and Schema

#### Wiring

