Product data sheet

Specifications



TeSys Deca reversing contactor -3P(3 NO) - AC-3 - <= 440 V 32 A -415 V AC coil

LC2D32N7

() Discontinued on: Oct 8, 2021

(!) Discontinued

Main

Range	TeSys
Product Name	TeSys Deca
Product Or Component Type	Reversing contactor
Device Short Name	LC2D
Contactor Application	Resistive load Motor control
Utilisation Category	AC-3 AC-1
Device Presentation	Preassembled with reversing power busbar
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[le] Rated Operational Current	32 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 50 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit
Motor Power Kw	7.5 kW at 220230 V AC 50 Hz 15 kW at 380400 V AC 50 Hz 15 kW at 415440 V AC 50 Hz 18.5 kW at 500 V AC 50 Hz 18.5 kW at 660690 V AC 50 Hz
Motor Power Hp (UI / Csa)	2 hp at 115 V AC 60 Hz for 1 phase motors 5 hp at 230/240 V AC 60 Hz for 1 phase motors 7.5 hp at 200/208 V AC 60 Hz for 3 phase motors 10 hp at 230/240 V AC 60 Hz for 3 phase motors 20 hp at 460/480 V AC 60 Hz for 3 phase motors 30 hp at 575/600 V AC 60 Hz for 3 phase motors
Control Circuit Type	AC 50/60 Hz
[Uc] Control Circuit Voltage	415 V AC 50/60 Hz
Auxiliary Contact Composition	1 NO + 1 NC
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C)) for signalling circuit 50 A (at 140 °F (60 °C)) for power circuit
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 550 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	550 A at 440 V for power circuit conforming to IEC 60947

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Life Is On Schneider

[Icw] Rated Short-Time Withstand Current	60 A 104 °F (40 °C) - 10 min for power circuit
Junent	138 A 104 °F (40 °C) - 1 min for power circuit
	260 A 104 °F (40 °C) - 10 s for power circuit 430 A 104 °F (40 °C) - 1 s for power circuit
	430 A 104 °F (40 °C) - 1 s for power circuit 100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
....... .	63 A gG at <= 690 V coordination type 1 for power circuit
	63 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2 mOhm - Ith 50 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1
	Power circuit 600 V CSA
	Power circuit 600 V UL
	Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA
	Signalling circuit 600 V UL
Electrical Durability	1.65 Mcvcles 32 A AC-3 <= 440 V
-	1.4 Mcycles 50 A AC-1 <= 440 V
Power Dissipation Per Pole	2 W AC-3
	5 W AC-1
Front Cover	With
Interlocking Type	Mechanical
Mounting Support	Rail Plate
Standards	CSA C22.2 No 14
	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1 IEC 60947-5-1
	UL 508
Product Certifications	000
	CSA
	LROS (Lloyds register of shipping)
	BV GL
	DNV
	GOST
	RINA
	UL
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible without
	cable end Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)flexible without
	cable end Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable
	end Control circuit screw clamp terminals 2 0.000.00 in ² (12.5 mm ²)flexible with cable
	end
	Control circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)solid
	Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)solid Power circuit screw clamp terminals 1 0.000.02 in ² (2.510 mm ²)flexible without
	cable end
	Power circuit screw clamp terminals 2 0.000.02 in² (2.510 mm²)flexible without
	cable end Power circuit screw clamp terminals 1 0.00…0.02 in² (1…10 mm²)flexible with cable
	end Power circuit screw clamp terminals 2 0.000.01 in ² (1.56 mm ²)flexible with cable
	end
	Power circuit screw clamp terminals 1 0.000.02 in ² (1.510 mm ²)solid Power circuit screw clamp terminals 2 0.000.02 in ² (2.510 mm ²)solid
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm
	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat \emptyset 6 mm
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2
Operating Time	1222 ms closing
	419 ms opening

Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz
Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	23 W 50/60 Hz
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Insulation Resistance	> 10 MOhm for signalling circuit

Environment

Ip Degree Of ProtectionIP20 front face IEC 60529Climatic WithstandIACS E10 IEC 60947-1 Annex Q category DProtective TreatmentTH IEC 60068-2-30Pollution Degree3Ambient Air Temperature For Operation-40140 °F (-4060 °C) 140158 °F (6070 °C) with deratingAmbient Air Temperature For Storage-76176 °F (-6080 °C)Operating Altitude09842.52 ft (03000 m)Fire Resistance1562 °F (850 °C) IEC 60695-2-1Flame RetardanceV1 conforming to UL 94Mechanical RobustnessVibrations contactor open2 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Shocks contactor open8 Gn for 11 msHeight3.35 in (85 mm)Width3.54 in (90 mm)Depth3.62 in (92 mm)		
IEC 60947-1 Annex Q category D Protective Treatment TH IEC 60068-2-30 Pollution Degree 3 Ambient Air Temperature For Operation -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating Ambient Air Temperature For Storage -76176 °F (-6080 °C) Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Vibrations contactor open8 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)	Ip Degree Of Protection	IP20 front face IEC 60529
Pollution Degree 3 Ambient Air Temperature For Operation -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating Ambient Air Temperature For Storage -76176 °F (-6080 °C) Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Vibrations contactor open8 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)	Climatic Withstand	
Ambient Air Temperature For Operation -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating Ambient Air Temperature For Storage -76176 °F (-6080 °C) Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Vibrations contactor open8 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)	Protective Treatment	TH IEC 60068-2-30
Operation 140158 °F (6070 °C) with derating Ambient Air Temperature For Storage -76176 °F (-6080 °C) Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Height 3.35 in (85 mm) Width 3.54 in (90 mm)	Pollution Degree	3
Storage Operating Altitude 09842.52 ft (03000 m) Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)		
Fire Resistance 1562 °F (850 °C) IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)		-76176 °F (-6080 °C)
Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)	Operating Altitude	09842.52 ft (03000 m)
Mechanical Robustness Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms Height 3.35 in (85 mm) Width 3.54 in (90 mm)	Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
Windth 3.35 in (85 mm) Width 3.54 in (90 mm)	Flame Retardance	V1 conforming to UL 94
Width 3.54 in (90 mm)	Mechanical Robustness	Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms
	Height	3.35 in (85 mm)
Depth 3.62 in (92 mm)	Width	3.54 in (90 mm)
	Depth	3.62 in (92 mm)
Net Weight 1.76 lb(US) (0.797 kg)	Net Weight	1.76 lb(US) (0.797 kg)

Ordering and shipping details

Category

22354-CTR, TESYS D, OPEN, 9-38A AC

Discount Schedule	112
Gtin	3389110391565
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.29 in (10.9 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	4.65 in (11.8 cm)
Package 1 Weight	28.75 oz (815 g)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Compliant
EU RoHS Declaration
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov