# Product data sheet

Specifications





() Discontinued

# Reversing contactor, TeSys K, 3P, AC-3, It or eq to 440V 6A, 1 NO, 220 to 230VAC coil

LC2K06105M7

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Walli	
Range	TeSys
Product Name	TeSys K
Product Or Component Type	Reversing contactor
Device Short Name	LC2K
Device Application	Control
Contactor Application	Motor control
Utilisation Category	AC-4 AC-3
Device Presentation	Preassembled with reversing power busbar
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit 690 V AC 50/60 Hz Signalling circuit <= 690 V AC 50/60 Hz
[le] Rated Operational Current	6 A at <= 440 V AC AC-3 for power circuit
Motor Power Kw	1.5 kW 220230 V AC 50/60 Hz 2.2 kW 380415 V AC 50/60 Hz 3 kW 440 V AC 50/60 Hz 3 kW 480 V AC 50/60 Hz 3 kW 500600 V AC 50/60 Hz 3 kW 660690 V AC 50/60 Hz
Control Circuit Type	AC 50/60 Hz
[Uc] Control Circuit Voltage	220230 V AC 50/60 Hz
Auxiliary Contact Composition	1 NO
[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	20 A (at 122 °F (50 °C)) for power circuit 10 A (at 122 °F (50 °C)) for signalling circuit
Irms Rated Making Capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947
Rated Breaking Capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 110 A at 220230 V conforming to IEC 60947 110 A at 380400 V conforming to IEC 60947 70 A at 660690 V conforming to IEC 60947

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Icw] Rated Short-Time Withstand	90 A 122 °F (50 °C) - 1 s for power circuit
Current	85  A 122 °F (50 °C) - 5 s for power circuit
	80 A 122 °F (50 °C) - 10 s for power circuit
	60 A 122 °F (50 °C) - 30 s for power circuit
	45 A 122 °F (50 °C) - 1 min for power circuit
	40 A 122 °F (50 °C) - 3 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
	20 A 122 °F (50 °C) - >= 15 min for power circuit
Associated Fuse Rating	25 A gG at <= 440 V for power circuit
	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit 600 V UL 508
	Power circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-5-1
	Signalling circuit 600 V UL 508
	Power circuit 600 V CSA C22.2 No 14
	Signalling circuit 600 V CSA C22.2 No 14
Electrical Durability	1.3 Mcycles 6 A AC-3 <= 440 V
2	1.3 Mcycles 6 A AC-3e <= 440 V
	0.05 Mcycles 36 A AC-4 <= 440 V
Interlocking Type	Mechanical
	Plate
Interlocking Type Mounting Support	
	Plate
	Plate
Mounting Support	Plate Rail
Mounting Support	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4
Mounting Support	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1
Mounting Support	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1
Mounting Support	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme CCC
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme CCC
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme CCC UL
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme CCC UL CSA
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme CCC UL CSA EAC
Mounting Support Standards	Plate Rail EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 CB Scheme CCC UL CSA EAC CE
Mounting Support Standards Product Certifications Connections - Terminals	Plate Rail           EN/IEC 60947-4-1           GB/T 14048.4           UL 60947-4-1           CSA C22.2 No 60947-4-1           JIS C8201-4-1           CB Scheme           CCC           UL           CSA           EAC           CE           UKCA
Mounting Support Standards Product Certifications	Plate Rail           EN/IEC 60947-4-1           GB/T 14048.4           UL 60947-4-1           CSA C22.2 No 60947-4-1           JIS C8201-4-1           CB Scheme           CCC           UL           CSA           EAC           CE           UKCA
Mounting Support Standards Product Certifications Connections - Terminals	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))
Mounting Support Standards Product Certifications Connections - Terminals Operating Time	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))         1020 ms coil energisation and NO closing         1020 ms coil de-energisation and NO opening
Mounting Support Standards Product Certifications Connections - Terminals	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))         1020 ms coil energisation and NO closing         1020 ms coil de-energisation and NO opening         B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1
Mounting Support Standards Product Certifications Connections - Terminals Operating Time	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))         1020 ms coil energisation and NO closing         1020 ms coil de-energisation and NO opening
Mounting Support Standards Product Certifications Connections - Terminals Operating Time Safety Reliability Level	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))         1020 ms coil energisation and NO closing         1020 ms coil de-energisation and NO opening         B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1         B10d = 2000000 cycles contactor with mechanical load EN/ISO 13849-1
Mounting Support Standards Product Certifications Connections - Terminals Operating Time	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))         1020 ms coil energisation and NO closing         1020 ms coil de-energisation and NO opening         B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1
Mounting Support Standards Product Certifications Connections - Terminals Operating Time Safety Reliability Level	Plate         Rail         EN/IEC 60947-4-1         GB/T 14048.4         UL 60947-4-1         CSA C22.2 No 60947-4-1         JIS C8201-4-1         CB Scheme         CCC         UL         CSA         EAC         CE         UKCA         solder pins 0.00 in (0.035 mm))         1020 ms coil energisation and NO closing         1020 ms coil de-energisation and NO opening         B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1         B10d = 2000000 cycles contactor with mechanical load EN/ISO 13849-1

## Complementary

Control Circuit Voltage Limits	Operational: 0.851.1 Uc (at <122 °F (50 °C)) Drop-out: 0.20.75 Uc (at <122 °F (50 °C))
Inrush Power In Va	30 VA (at 68 °F (20 °C))
Hold-In Power Consumption In Va	4.5 VA (at 68 °F (20 °C))
Heat Dissipation	1.3 W
Auxiliary Contacts Type	Instantaneous 1 NO
Signalling Circuit Frequency	<= 400 Hz
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit

Non Overlap Distance	0.02 in (0.5 mm)
Insulation Resistance	> 10 MOhm for signalling circuit

## Environment

Ip Degree Of Protection	IP20 VDE 0106	
Protective Treatment	TC IEC 60068 TC DIN 50016	
Ambient Air Temperature For Operation	-13122 °F (-2550 °C)	
Ambient Air Temperature For Storage	-58176 °F (-5080 °C)	
Operating Altitude	6561.68 ft (2000 m) without derating	
Flame Retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	
Mechanical Robustness	Shocks contactor closed, on X axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Y axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Z axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on X axis6 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Y axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6 Vibrations contactor opened2 Gn, 5300 Hz IEC 60068-2-6	
Height	2.28 in (58 mm)	
Width	3.54 in (90 mm)	
Depth	2.24 in (57 mm)	
Net Weight	0.86 lb(US) (0.39 kg)	

## Ordering and shipping details

Category	US10I1222327
Discount Schedule	0112
Gtin	3389110491470
Returnability	No

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.56 in (6.5 cm)
Package 1 Width	3.74 in (9.5 cm)
Package 1 Length	2.36 in (6.0 cm)
Package 1 Weight	14.76 oz (418.5 g)

#### **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information