Product data sheet

Specification





TeSys

Contactor, TeSys K, 3P, AC-3, It or eq to 440V, 6A, 1 NC aux, 24VDC coil

LP4K0601BW3

Product availability: Stock - Normally stocked in distribution facility

Price*: 92.00 USD

Main Range

Product Or Component Type	Contactor
Device Short Name	LP4K
Contactor Application	Motor control
Complementary	
Utilisation Category	AC-3 AC-3e AC-4
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC <= 400 Hz Signalling circuit <= 690 V AC <= 400 Hz
[le] Rated Operational Current	6 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 6 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
Control Circuit Type	DC wide range
[Uc] Control Circuit Voltage	24 V DC
Motor Power Kw	1.5 kW 220230 V AC 50/60 Hz AC-3 2.2 kW 380415 V AC 50/60 Hz AC-3 3 kW 440/690 V AC 50/60 Hz AC-3 1.5 kW 220230 V AC 50/60 Hz AC-3e 2.2 kW 380415 V AC 50/60 Hz AC-3e 3 kW 440/690 V AC 50/60 Hz AC-3e 1.5 kW 220230 V AC 50/60 Hz AC-3e 1.5 kW 220230 V AC 50/60 Hz AC-4 2.2 kW 380415 V AC 50/60 Hz AC-4 3 kW 440/690 V AC 50/60 Hz AC-4
Auxiliary Contact Composition	1 NC
[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	20 A (at 140 °F (60 °C)) for power circuit 10 A (at 122 °F (50 °C)) for signalling circuit
Irms Rated Making Capacity	110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947
Rated Breaking Capacity	110 A at 220230 V conforming to IEC 60947 110 A at 380400 V conforming to IEC 60947 110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 70 A at 660690 V conforming to IEC 60947

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

-	
[Icw] Rated Short-Time Withstand	90 A 122 °F (50 °C) - 1 s for power circuit
Current	85 A 122 °F (50 °C) - 5 s for power circuit
	80 A 122 °F (50 °C) - 10 s for power circuit
	60 A 122 °F (50 °C) - 30 s for power circuit
	45 A 122 °F (50 °C) - 1 min for power circuit
	40 A 122 °F (50 °C) - 3 min for power circuit
	20 A 122 °F (50 °C) - >= 15 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
Associated Fuse Rating	25 A gG at <= 440 V for power circuit
· ·	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
According to the second	
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit 600 V UL 508
	Power circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-5-1
	Signalling circuit 600 V UL 508
	Power circuit 600 V CSA C22.2 No 14
	Signalling circuit 600 V CSA C22.2 No 14
Insulation Resistance	> 10 MOhm for signalling circuit
Inrush Power In W	1.8 W 68 °F (20 °C))
Hold-In Power Consumption In W	1.8 W 68 °F (20 °C)
Heat Dissipation	1.8 W
Control Circuit Voltage Limite	Operationals 0.7 A 0.11s (at 4400 %F (F0 %O))
Control Circuit Voltage Limits	Operational: 0.71.3 Uc (at <122 °F (50 °C)) Drop-out: >= 0.10 Uc (at <122 °F (50 °C))
Connections - Terminals	screw clamp terminals 1 0.000.01 in² (1.54 mm²)solid
	screw clamp terminals 1 0.000.01 in² (0.754 mm²)flexible without cable end
	screw clamp terminals 1 0.000.00 in ² (0.342.5 mm ²)flexible with cable end
	screw clamp terminals 2 0.000.01 in² (1.54 mm²)solid
	, , , , , , , , , , , , , , , , , , , ,
	screw clamp terminals 2 0.000.01 in2 (0.754 mm2)flexible without cable end
	screw clamp terminals 2 0.000.01 in² (0.754 mm²)flexible without cable end screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end
	· · · · · · · · · · · · · · · · · · ·
	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end
Maximum Operating Rate	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end
Maximum Operating Rate Coil Technology	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end
·	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h
Coil Technology	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor
Coil Technology Auxiliary Contacts Type	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC
Coil Technology Auxiliary Contacts Type Minimum Switching Current	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit Plate Rail
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level Mechanical Durability	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 30 Mcycles
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level Mechanical Durability	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 30 Mcycles 1.3 Mcycles 6 A AC-3 <= 440 V 1.3 Mcycles 6 A AC-3 <= 440 V
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level Mechanical Durability	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 30 Mcycles
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level Mechanical Durability	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 30 Mcycles 1.3 Mcycles 6 A AC-3 <= 440 V 1.3 Mcycles 36 A AC-4 <= 440 V 0.05 Mcycles 36 A AC-4 <= 440 V
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Electrical Durability Height	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 30 Mcycles 1.3 Mcycles 6 A AC-3 <= 440 V 1.3 Mcycles 6 A AC-3 <= 440 V 1.3 Mcycles 36 A AC-4 <= 440 V 2.28 in (58 mm)
Coil Technology Auxiliary Contacts Type Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Electrical Durability	screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.00 in² (1.5 mm²)flexible with cable end 3600 cyc/h Built-in bidirectional peak limiting diode suppressor Instantaneous 1 NC 5 mA for signalling circuit 17 V for signalling circuit Plate Rail 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2 1020 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 30 Mcycles 1.3 Mcycles 6 A AC-3 <= 440 V 1.3 Mcycles 36 A AC-4 <= 440 V 0.05 Mcycles 36 A AC-4 <= 440 V

Net Weight	0.52 lb(US) (0.235 kg)

Environment

LIIVII OIIIIIOIIC	
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4
Product Certifications	CB Scheme CCC UL CSA EAC CE UKCA
Ip Degree Of Protection	IP2X
Ambient Air Temperature For Operation	-13122 °F (-2550 °C)
Ambient Air Temperature For Storage	-58176 °F (-5080 °C)
Operating Altitude	6561.68 ft (2000 m) without derating
Flame Retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102

Ordering and shipping details

Category	US10I1222321
Discount Schedule	0112
Gtin	3389110428551
Returnability	Yes
Country Of Origin	ID

Packing Units

PCE
1
2.60 in (6.600 cm)
1.89 in (4.800 cm)
2.44 in (6.200 cm)
7.80 oz (221.000 g)
S02
40
5.91 in (15.000 cm)
11.81 in (30.000 cm)
15.75 in (40.000 cm)
20.17 lb(US) (9.148 kg)
P06
640
29.53 in (75.000 cm)

Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	351.32 lb(US) (159.355 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
Ø	Mercury Free	
9	Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov


Dimensions Drawings

Dimensions

Contactors LC1 K, LP1 K, LP4 K: Mounting on Panel




Contactors LC1 K, LP1 K, LP4 K: Mounting on Rail AM1 DP200 or AM1 DE200 (35 mm)



Connections and Schema

Wiring

3-Pole Reversing Contactors with Screw Clamp Connections: 3P + N/O



3-Pole Reversing Contactors with Screw Clamp Connections: 3P + N/C

