# **Product data sheet**

Specification





# TeSys Deca thermal overload relays, 23...32A, class 20

LR2D3553

Product availability: Stock - Normally stocked in distribution facility

Price\*: 107.00 USD

#### Main

Range	TeSys
Product Name	TeSys LRD TeSys Deca
Product Or Component Type	Differential thermal overload relay
Device Short Name	LR2D
Relay Application	Motor protection
Product Compatibility	LC1D95 LC1D80
Network Type	AC DC
Thermal Overload Class	Class 20 IEC 60947-4-1
Thermal Protection Adjustment Range	2332 A
[Ui] Rated Insulation Voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 690 V IEC 60947-4-1

#### Complementary

Network Frequency	0400 Hz
Mounting Support	Plate, with specific accessories
	Rail, with specific accessories
	Under contactor
Tripping Threshold	1.14 +/- 0.06 Ir IEC 60947-4-1
Auxiliary Contact Composition	1 NO + 1 NC
[Ith] Conventional Free Air Thermal Current	5 A signalling circuit
Permissible Current	0.72 A 500 V AC-15 signalling circuit
	0.06 A 440 V DC-13 signalling circuit
[Ue] Rated Operational Voltage	1000 V AC 0400 Hz power circuit IEC 60947-4-1
Associated Fuse Rating	4 A gG for signalling circuit
	4 A BS for signalling circuit
[Uimp] Rated Impulse Withstand Voltage	6 kV
Phase Failure Sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0
Control Type	Red push-button stop
	Blue push-button reset
Temperature Compensation	-4140 °F (-2060 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Connections - Terminals	Power circuit screw clamp terminals 1 0.010.05 in² (435 mm²) flexible without cable end		
	Power circuit screw clamp terminals 1 0.010.05 in² (435 mm²) flexible with cable end		
	Power circuit screw clamp terminals 1 0.010.05 in² (435 mm²) solid without cable end		
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible without cable end		
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible with cable end		
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) solid without cable end		
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.66 lbf.in (9 N.m) screw clamp terminals		
Height	3.94 in (100 mm)		
Width	2.95 in (75 mm)		
Depth	4.76 in (121 mm)		
Net Weight	1.18 lb(US) (0.535 kg)		

#### **Environment**

Climatic Withstand	IACS E10	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Ambient Air Temperature For Operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1	
Ambient Air Temperature For Storage	-76158 °F (-6070 °C)	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations6 Gn IEC 60068-2-6 Shocks15 Gn for 11 ms IEC 60068-2-7	
Dielectric Strength	2.2 kV 50 Hz IEC 60947-1	
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1	
Product Certifications	IEC UL CSA EAC DNV-GL LROS (Lloyds register of shipping) UKCA	

## Ordering and shipping details

Category	US10I1222347
Discount Schedule	0112
Gtin	3389110229080
Returnability	Yes
Country Of Origin	FR

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3 07 in (7 8 cm)

Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	4.65 in (11.8 cm)
Package 1 Weight	18.10 oz (513.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	12
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	14.33 lb(US) (6.501 kg)

# **Contractual warranty**

Warranty 18 months

### Sustainability Green Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

	Reach Free Of Svhc	
<b>9</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

REACh Declaration
Compliant
EU RoHS Declaration
China RoHS declaration
Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov