# **Product data sheet**

Specification





# TeSys Deca thermal overload relays, 55...70A - class 20

LR2D3561

Product availability: Stock - Normally stocked in distribution facility

Price\*: 127.00 USD

### Main

| Range                               | TeSys  |
|-------------------------------------|--|
| Product Name                        | TeSys LRD<br>TeSys Deca  |
| Product Or Component Type           | Differential thermal overload relay  |
| Device Short Name                   | LR2D   |
| Relay Application                   | Motor protection   |
| Product Compatibility               | LC1D95<br>LC1D80   |
| Network Type                        | AC<br>DC   |
| Thermal Overload Class              | Class 20 IEC 60947-4-1   |
| Thermal Protection Adjustment Range | 5570 A   |
| [Ui] Rated Insulation Voltage       | Power circuit 600 V CSA Power circuit 600 V UL Power circuit 690 V IEC 60947-4-1 |

## Complementary

| Network Frequency                              | 0400 Hz  |
|--|--|
| Mounting Support                               | Plate, with specific accessories Rail, with specific accessories Under contactor |
| Tripping Threshold                             | 1.14 +/- 0.06 Ir IEC 60947-4-1   |
| Auxiliary Contact Composition                  | 1 NO + 1 NC  |
| [Ith] Conventional Free Air<br>Thermal Current | 5 A signalling circuit   |
| Permissible Current                            | 0.72 A 500 V AC-15 signalling circuit<br>0.06 A 440 V DC-13 signalling circuit   |
| [Ue] Rated Operational Voltage                 | 1000 V AC 0400 Hz power circuit IEC 60947-4-1                                    |
| Associated Fuse Rating                         | 4 A gG for signalling circuit 4 A BS for signalling circuit                      |
| [Uimp] Rated Impulse Withstand<br>Voltage      | 6 kV   |
| Phase Failure Sensitivity                      | Tripping current 130 % of Ir on two phase, the last one at 0                     |
| Control Type                                   | Red push-button stop<br>Blue push-button reset                                   |
| Temperature Compensation                       | -4140 °F (-2060 °C)  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Connections - Terminals | Power circuit screw clamp terminals 1 0.010.05 in² (435 mm²) flexible without cable end  Power circuit screw clamp terminals 1 0.010.05 in² (435 mm²) flexible with cable end |  |  |
|-------------------------|---|--|--|
|                         |   |  |  |
|                         | Power circuit screw clamp terminals 1 0.010.05 in² (435 mm²) solid without cable end  |  |  |
|                         | Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible without cable end  |  |  |
|                         | Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible with cable end   |  |  |
|                         | Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) solid without cable end   |  |  |
| Tightening Torque       | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.66 lbf.in (9 N.m) screw clamp terminals   |  |  |
| Height                  | 3.94 in (100 mm)  |  |  |
| Width                   | 2.95 in (75 mm)   |  |  |
| Depth                   | 4.76 in (121 mm)  |  |  |
| Net Weight              | 1.18 lb(US) (0.535 kg)  |  |  |

## **Environment**

| Climatic Withstand                    | IACS E10   |  |
|---------------------------------------|--|--|
| Ip Degree Of Protection               | IP20 conforming to IEC 60529   |  |
| Ambient Air Temperature For Operation | -4140 °F (-2060 °C) without derating IEC 60947-4-1   |  |
| Ambient Air Temperature For Storage   | -76158 °F (-6070 °C)   |  |
| Flame Retardance                      | V1 conforming to UL 94   |  |
| Mechanical Robustness                 | Vibrations6 Gn IEC 60068-2-6<br>Shocks15 Gn for 11 ms IEC 60068-2-7  |  |
| Dielectric Strength                   | 2.2 kV 50 Hz IEC 60947-1   |  |
| Standards                             | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-4-1<br>CSA C22.2 No 60947-5-1 |  |
| Product Certifications                | IEC UL CSA EAC DNV-GL LROS (Lloyds register of shipping) UKCA  |  |

## Ordering and shipping details

| Category               | US10I1222347  |
|------------------------|---------------|
| Discount Schedule 0l12 |               |
| Gtin                   | 3389110229127 |
| Returnability          | Yes           |
| Country Of Origin      | US            |

## **Packing Units**

| Unit Type Of Package 1       | PCE                |
|------------------------------|--------------------|
| Number Of Units In Package 1 | 1                  |
| Package 1 Height             | 3.35 in (8.500 cm) |

| Package 1 Width              | 3.07 in (7.800 cm)      |
|------------------------------|-------------------------|
| Package 1 Length             | 4.65 in (11.800 cm)     |
| Package 1 Weight             | 18.34 oz (520.000 g)    |
| Unit Type Of Package 2       | S02                     |
| Number Of Units In Package 2 | 12                      |
| Package 2 Height             | 5.91 in (15.000 cm)     |
| Package 2 Width              | 11.81 in (30.000 cm)    |
| Package 2 Length             | 15.75 in (40.000 cm)    |
| Package 2 Weight             | 14.55 lb(US) (6.600 kg) |

# **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

|          | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>9</b> | Toxic Heavy Metal Free     |     |
| <b>⊘</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| REACh Declaration   |
|---|
| Compliant   |
| EU RoHS Declaration   |
| China RoHS declaration  |
| Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Product Environmental Profile   |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| End of Life Information   |
| WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
|   |