Product data sheet

Specifications





① Discontinued

Thermal overload relay, TeSys Deca, 690VAC, 23 to 32A, 1NO+1NC, class 10A, EverLink springs terminals

LRD3323

() Discontinued on: Dec 31, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

TeSys	
TeSys LRD TeSys Deca	
Differential thermal overload relay	
LRD	
Motor protection	
LC1D65A LC1D40A LC1D50A	
AC DC	
Class 10A IEC 60947-4-1	
rmal Protection Adjustment 2332 A ge	
Power circuit 600 V CSA Power circuit 600 V UL Power circuit 690 V IEC 60947-4-1	

Complementary

Network Frequency	0400 Hz	
Mounting Support	Plate, with specific accessories Rail, with specific accessories Under contactor	
Tripping Threshold	1.14 +/- 0.06 Ir IEC 60947-4-1	
Auxiliary Contact Composition	1 NO + 1 NC	
[Ith] Conventional Free Air Thermal Current	5 A signalling circuit	
Permissible Current	0.95 A 380 V AC-15 signalling circuit 0.06 A 440 V DC-13 signalling circuit	
[Ue] Rated Operational Voltage	690 V AC 0400 Hz power circuit IEC 60947-4-1	
Associated Fuse Rating	4 A gG for signalling circuit 4 A BS for signalling circuit	
[Uimp] Rated Impulse Withstand Voltage	6 kV	
Phase Failure Sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Control Type	Red push-button stop Blue push-button reset	
Temperature Compensation	-4140 °F (-2060 °C)	
Connections - Terminals	Power circuit EverLink BTR screw connectors 1 0.000.05 in ² (135 mm ²) flexible without cable end Power circuit EverLink BTR screw connectors 1 0.000.05 in ² (135 mm ²) flexible with cable end Power circuit EverLink BTR screw connectors 1 0.000.05 in ² (135 mm ²) solid without cable end Control circuit spring terminals 1 0.000.00 in ² (12.5 mm ²) solid without cable end Control circuit spring terminals 1 0.000.00 in ² (12.5 mm ²) flexible without cable	
Tightening Torque	end Power circuit 44.25 lbf.in (5 N.m) EverLink BTR screw connectors	
Height	4.84 in (123 mm)	
Width	dth 2.17 in (55 mm)	
Depth	th 4.84 in (123 mm)	
let Weight 0.83 lb(US) (0.375 kg)		

Environment

Climatic Withstand	IACS E10
Ip Degree Of Protection	IP20 conforming to IEC 60529
Ambient Air Temperature For Operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1
Ambient Air Temperature For Storage	-76158 °F (-6070 °C)
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Shocks15 Gn for 11 ms IEC 60068-2-7 Vibrations4 gn IEC 60068-2-6
Dielectric Strength	1.89 kV 50 Hz IEC 60947-1
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495
Product Certifications	IEC UL CSA CCC EAC DNV-GL RMRS EU-RO MR LROS (Lloyds register of shipping) ATEX INERIS UKCA

Ordering and shipping details

Category	US10I1222347	
Discount Schedule	0 12	
Gtin	3389119215626	
Returnability	No	
Country Of Origin	FR	

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.56 in (6.5 cm)
Package 1 Width	4.33 in (11 cm)
Package 1 Length	5.51 in (14 cm)
Package 1 Weight	15.10 oz (428 g)
Unit Type Of Package 2	\$02
Number Of Units In Package 2	13
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	13.27 lb(US) (6.019 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

9	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov