## Product data sheet

Specifications





# TeSys Deca thermal overload relays , 110...140A , class 10A

LRD4369

Product availability: Stock - Normally stocked in distribution facility

#### Price\*: 362.00 USD

#### Main

| Range                                  | TeSys                               |
|--|-------------------------------------|
| Product Name                           | TeSys LRD<br>TeSys Deca             |
| Product Or Component Type              | Differential thermal overload relay |
| Device Short Name                      | LRD                                 |
| Relay Application                      | Motor protection                    |
| Product Compatibility                  | LC1D150                             |
| Network Type                           | DC<br>AC                            |
| Thermal Overload Class                 | Class 10A IEC 60947-4-1             |
| Thermal Protection Adjustment<br>Range | 110140 A                            |
| [Ui] Rated Insulation Voltage          | Power circuit 1000 V IEC 60947-4-1  |

### Complementary

| Network Frequency              | 0400 Hz  |
|--------------------------------|--|
| Mounting Support               | Plate, with specific accessories                             |
|                                | Rail, with specific accessories                              |
|                                | Under contactor  |
|                                |  |
| Tripping Threshold             | 1.14 +/- 0.06 lr IEC 60947-4-1                               |
| Auxiliary Contact Composition  | 1 NO + 1 NC  |
|                                |  |
| [Ith] Conventional Free Air    | 5 A signalling circuit                                       |
| Thermal Current                |  |
| Permissible Current            | 0.06 A 440 V DC-13 signalling circuit                        |
|                                | 0.12 A 600 V AC-15 signalling circuit                        |
| [Ue] Rated Operational Voltage | 1000 V AC 0400 Hz power circuit IEC 60947-4-1                |
| Associated Fuse Rating         | 4 A gG for signalling circuit                                |
|                                | 4 A BS for signalling circuit                                |
|                                |  |
| [Uimp] Rated Impulse Withstand | 6 kV IEC 60947-1   |
| Voltage                        |  |
| Phase Failure Sensitivity      | Tripping current 130 % of Ir on two phase, the last one at 0 |
|                                | ··· -  |
| Control Type                   | Red push-button stop   |
|                                | Blue push-button reset                                       |
| Temperature Compensation       | -4140 °F (-2060 °C)  |
|                                |  |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Connections - Terminals | Power circuit screw clamp terminals 1 0.010.05 in <sup>2</sup> (435 mm <sup>2</sup> ) flexible with cable end            |
|-------------------------|--|
|                         | Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible without cable end      |
|                         | Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible with<br>cable end      |
|                         | Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) solid without<br>cable end      |
|                         | Power circuit screw clamp terminals 1 0.010.08 in <sup>2</sup> (450 mm <sup>2</sup> ) flexible without<br>cable end      |
|                         | Power circuit screw clamp terminals 1 0.010.08 in <sup>2</sup> (450 mm <sup>2</sup> ) solid without cable end            |
| Tightening Torque       | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals<br>Power circuit 79.66 lbf.in (9 N.m) screw clamp terminals |
| Depth                   | 5.20 in (132 mm)   |
| Net Weight              | 1.98 lb(US) (0.9 kg)   |

## Environment

| Climatic Withstand                       | IACS E10   |
|--|--|
| Ip Degree Of Protection                  | IP20 conforming to IEC 60529   |
| Ambient Air Temperature For<br>Operation | -4140 °F (-2060 °C) without derating IEC 60947-4-1                               |
| Ambient Air Temperature For<br>Storage   | -76158 °F (-6070 °C)   |
| Flame Retardance                         | V1 conforming to UL 94   |
| Mechanical Robustness                    | Vibrations6 Gn IEC 60068-2-6<br>Shocks15 Gn for 11 ms IEC 60068-2-7              |
| Dielectric Strength                      | 2.2 kV 50 Hz IEC 60947-1   |
| Standards                                | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>GB/T 14048.4<br>GB/T 14048.5<br>EN 50495 |
| Product Certifications                   | IEC<br>CCC<br>EAC<br>ATEX INERIS   |

## Ordering and shipping details

| Category          | US10I1222347  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| Gtin              | 3389110523355 |
| Returnability     | Yes           |
| Country Of Origin | US            |

## **Packing Units**

| -                            |                      |
|------------------------------|----------------------|
| Unit Type Of Package 1       | PCE                  |
| Number Of Units In Package 1 | 1                    |
| Package 1 Height             | 5.43 in (13.800 cm)  |
| Package 1 Width              | 4.13 in (10.500 cm)  |
| Package 1 Length             | 6.10 in (15.500 cm)  |
| Package 1 Weight             | 29.38 oz (833.000 g) |
| Unit Type Of Package 2       | S03                  |

| Number Of Units In Package 2 | 10                        |
|------------------------------|---------------------------|
| Package 2 Height             | 11.81 in (30.000 cm)      |
| Package 2 Width              | 11.81 in (30.000 cm)      |
| Package 2 Length             | 15.75 in (40.000 cm)      |
| Package 2 Weight             | 19.48 lb(US) (8.835 kg)   |
| Unit Type Of Package 3       | P06                       |
| Number Of Units In Package 3 | 80                        |
| Package 3 Height             | 29.53 in (75.000 cm)      |
| Package 3 Width              | 23.62 in (60.000 cm)      |
| Package 3 Length             | 31.50 in (80.000 cm)      |
| Package 3 Weight             | 171.26 lb(US) (77.680 kg) |

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

| Toxic Heavy Metal Free     |     |
|----------------------------|-----|
| Mercury Free               |     |
| Rohs Exemption Information | Yes |

## **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant<br>EU RoHS Declaration  |
| China Rohs Regulation     | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Environmental Disclosure  | Product Environmental Profile   |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |