# Product data sheet





Advanced control unit, TeSys Ultra, 4.5A to 18A, 1P motors, protection & diagnostic, class 10, coil 24VAC

LUCC18B

Discontinued on: Jul 12, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range	TeSys
Range Of Product	TeSys U
Product Name	TeSys U
Device Short Name	LUCC
Product Or Component Type	Advanced control unit
Device Application	Motor control Motor protection
Product Specific Application	Basic protection and advanced functions, communication
Main Function Available	Protection against overload and short-circuit Manual reset Earth fault protection Protection against phase failure and phase imbalance
Product Compatibility	Power base LUB32 Power base LUB38 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B32B
[Ue] Rated Operational Voltage	690 V AC
Network Frequency	4060 Hz
Load Type	Single-phase motor
Utilisation Category	AC-41 AC-43 AC-44
Motor Power Kw	4 kW 400440 V AC 50/60 Hz 1 phase
Rated Motor Current Adjustment Range	4.518 A
Thermal Overload Class	Class 10 4060 Hz -13131 °F (-2555 °C) IEC 60947-6-2 Class 10 4060 Hz -13131 °F (-2555 °C) UL 508
Tripping Threshold	14.2 x lr +/- 20 %
[Uc] Control Circuit Voltage	24 V AC

#### Complementary

**Control Circuit Voltage Limits** 20...26.5 V AC 24 V in operation 14.5 V AC 24 V drop-out

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.



Typical Current Consumption	220 mA 24 V AC I maximum while closing with LUB32 220 mA 24 V AC I maximum while closing with LUB38
	90 mA 24 V AC I rms sealed with LUB32 90 mA 24 V AC I rms sealed with LUB38
Heat Dissipation	3 W control circuit with LUB32 3 W control circuit with LUB38
Operating Time	
Operating Time	35 ms opening with LUB32 control circuit 35 ms opening with LUB38 control circuit
	70 ms closing with LUB32 control circuit
	70 ms closing with LUB38 control circuit
Reset	Manual reset
Standards	EN 60947-6-2
	IEC 60947-6-2
	UL 60947-4-1, with phase barrier CSA C22.2 No 60947-4-1, with phase barrier
Product Certifications	CE
Froduct Certifications	UL UL
	CSA
	CCC
	EAC
	ASEFA
	ATEX Marine
	690 V IEC 60947-6-2
	600 V UL 60947-4-1
	600 V CSA C22.2 No 60947-4-1
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947-6-2
Safe Separation Of Circuit	400 V SELV between the control and auxiliary circuits IEC 60947-1 400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1
Fixing Mode	Plug-in (front face)
Width	1.77 in (45 mm)
	2.60 in (66 mm)
Depth	2.36 in (60 mm)
Compatibility Code	LUCC
Environment	
Ip Degree Of Protection	IP20 front panel and wired terminals IEC 60947-1 IP20 other faces IEC 60947-1 IP40 front panel outside connection zone IEC 60947-1
Protective Treatment	TH IEC 60068
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)
Operating Altitude	6561.68 ft (2000 m)

Ip Degree Of Protection	IP20 front panel and wired terminals IEC 60947-1 IP20 other faces IEC 60947-1 IP40 front panel outside connection zone IEC 60947-1	
Protective Treatment	TH IEC 60068	
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)	
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)	
Operating Altitude	6561.68 ft (2000 m)	
Fire Resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12	
Shock Resistance	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27	
Vibration Resistance	2 gn 5300 Hz power poles open IEC 60068-2-6 4 gn 5300 Hz power poles closed IEC 60068-2-6	
Resistance To Electrostatic Discharge	8 kV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2	
Non-Dissipating Shock Wave	1 kV serial mode IEC 60947-6-2 2 kV common mode IEC 60947-6-2	
Resistance To Radiated Fields	9.14 V/m (10 V/m) 3 IEC 61000-4-3	

Resistance To Fast Transients	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Immunity To Radioelectric Fields	10 V IEC 61000-4-6
Immunity To Microbreaks	3 ms
Immunity To Voltage Dips	70 % / 500 ms IEC 61000-4-11

# Ordering and shipping details

Category	US10I1122397
Discount Schedule	0111
Gtin	3389110364590
Returnability	No
Country Of Origin	US

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.01 in (5.1 cm)
Package 1 Width	3.19 in (8.1 cm)
Package 1 Length	3.39 in (8.6 cm)
Package 1 Weight	4.94 oz (140 g)

### **Contractual warranty**

Warranty 18 months

### Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>Ø</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>Ø</b>	Pvc Free
<b>⊘</b>	Halogen Free Plastic Parts Product

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information