Product data sheet

Specifications





TeSys F - contactor coil - LX1FJ -240 V AC 40...400 Hz

LX1FJ240

(!) To be discontinued on: Dec 31, 2028

① To be discontinued

Product availability: Stock - Normally stocked in distribution facility

Price*: 344.40 USD

Main

| Range | TeSys |
|------------------------------|---|
| Product Or Component Type | Contactor coil |
| Device Short Name | LX1FJ |
| Range Compatibility | TeSys TeSys F LC1F contactor |
| Product Compatibility | LC1F400 |
| Control Circuit Type | AC 40400 Hz |
| [Uc] Control Circuit Voltage | 240 V AC 40400 Hz |
| Inductance Of Closed Circuit | 6.4 H |
| Average Resistance | 47.5 Ohm inrush 68 °F (20 °C) 1320 Ohm holding 68 °F (20 °C) |
| Operating Time | 100170 ms opening 4075 ms closing |
| Mechanical Durability | 10 Mcycles |
| Maximum Operating Rate | 2400 cyc/h 131 °F (55 °C) |
| | |

Complementary

| Coil Technology | Without built-in suppressor module |
|---------------------------------|--|
| Control Circuit Voltage Limits | Operational 0.851.1 Uc 40400 Hz 131 °F (55 °C)) Drop-out 0.30.5 Uc 40400 Hz 131 °F (55 °C)) |
| Inrush Power In Va | 1075 VA 40400 Hz cos phi 0.9 (at 68 °F (20 °C)) |
| Hold-In Power Consumption In Va | 15 VA 40400 Hz cos phi 0.3 (at 68 °F (20 °C)) |
| Heat Dissipation | 14 W 40400 Hz |

Environment

| Ambient Air Temperature For Operation | 23131 °F (-555 °C) |
|--|--------------------|
| Net Weight | 2.20 lb(US) (1 kg) |

Ordering and shipping details

| Category | US10I1222341 | |
|-------------------|---------------|--|
| Discount Schedule | 0112 | |
| Gtin | 3389110082043 | |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Returnability | Yes |
|-------------------|-----|
| Country Of Origin | FR |

Packing Units

| • | | |
|------------------------------|------------------------|--|
| Unit Type Of Package 1 | PCE | |
| Number Of Units In Package 1 | 1 | |
| Package 1 Height | 7.40 in (18.796 cm) | |
| Package 1 Width | 3.60 in (9.144 cm) | |
| Package 1 Length | 3.90 in (9.906 cm) | |
| Package 1 Weight | 2.43 lb(US) (1.102 kg) | |
| Unit Type Of Package 2 | S03 | |
| Number Of Units In Package 2 | 6 | |
| Package 2 Height | 11.81 in (30 cm) | |
| Package 2 Width | 11.81 in (30 cm) | |
| Package 2 Length | 15.75 in (40 cm) | |
| Package 2 Weight | 16.25 lb(US) (7.37 kg) | |

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |