Product data sheet

Specifications





TeSys F - contactor coil - LX1FK - 380...400V AC 40...400 Hz

LX1FK380

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 432.00 USD

Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX1FK
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F500
Control Circuit Type	AC 40400 Hz
[Uc] Control Circuit Voltage	380400 V AC 40400 Hz
Inductance Of Closed Circuit	14.7 H
Average Resistance	112 Ohm inrush 68 °F (20 °C) 2980 Ohm holding 68 °F (20 °C)
Operating Time	100170 ms opening 4075 ms closing
Mechanical Durability	10 Mcycles
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)

Complementary

Coil Technology	Without built-in suppressor module	
Control Circuit Voltage Limits	Operational 0.851.1 Uc 40400 Hz 131 °F (55 °C)) Drop-out 0.30.5 Uc 40400 Hz 131 °F (55 °C))	
Inrush Power In Va	1100 VA 40400 Hz cos phi 0.9 (at 68 °F (20 °C))	
Hold-In Power Consumption In Va	18 VA 40400 Hz cos phi 0.3 (at 68 °F (20 °C))	
Heat Dissipation	18 W 40400 Hz	

Environment

Ambient Air Temperature For Operation	23131 °F (-555 °C)
Net Weight	2.54 lb(US) (1.15 kg)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0112
Gtin	3389110082265
Returnability	No
Country Of Origin	CZ

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Packing Units

V	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.94 in (10 cm)
Package 1 Width	4.53 in (11.5 cm)
Package 1 Length	8.90 in (22.6 cm)
Package 1 Weight	2.65 lb(US) (1.203 kg)
Unit Type Of Package 2	\$03
Number Of Units In Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	16.88 lb(US) (7.656 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information