Product data sheet

Specifications

TeSys F - contactor coil - LX1FL - 200...208 V AC 40...400 Hz

LX1FL200

Product availability: Stock - Normally stocked in distribution facility

Price*: 716.40 USD

Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX1FL
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F1250 LC1F630
Control Circuit Type	AC 40...400 Hz
[Uc] Control Circuit Voltage	200...208 V AC 40...400 Hz
Inductance Of Closed Circuit	2.65 H
Average Resistance	20.5 Ohm inrush 68 °F (20 °C) 605 Ohm holding 68 °F (20 °C)
Operating Time	100...200 ms opening 40...80 ms closing
Mechanical Durability	5 Mcycles
Maximum Operating Rate	1200 cyc/h 131 °F (55 °C)

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational 0.85...1.1 Uc 40...400 Hz 131 °F (55 °C)) Drop-out 0.25...0.5 Uc 40...400 Hz 131 °F (55 °C))
Inrush Power In Va	1650 VA 40...400 Hz cos phi 0.9 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	22 VA 40...400 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	20 W 40...400 Hz

Environment

Ambient Air Temperature For Operation	23…131 °F (-5…55 °C)
Net Weight	3.31 lb(US) (1.5 kg)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
Gtin	3389110225587
Returnability	Yes

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.30 in (10.922 cm)
Package 1 Width	5.30 in (13.462 cm)
Package 1 Length	9.40 in (23.876 cm)
Package 1 Weight	3.19 lb(US) (1.447 kg)

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information