Product data sheet

Specifications





motion servo drive, Lexium 28, single and three phase, 200 to 240V, 400W

LXM28AU04M3X

Product availability: Stock - Normally stocked in distribution facility

Price*: 640.00 USD

Main

| Range Of Product | Lexium 28 |
|---------------------------|---|
| Product Or Component Type | Motion servo drive |
| Device Short Name | LXM28A |
| Format Of The Drive | Compact housing |
| Line Current | 3.8 A 211.6 % 220 V, single phase 3.8 A 183.7 % 220 V, three phase |

Complementary

| Phase | Three phase Single phase |
|---------------------------|--|
| [Us] Rated Supply Voltage | 200240 V - 1015 %)three phase 200240 V - 2015 %)single phase |
| Supply Voltage Limits | 200255 V three phase 170255 V single phase |
| Supply Frequency | 50/60 Hz - 55 % |
| Network Frequency | 47.563 Hz |
| Emc Filter | Without EMC filter |
| Continuous Output Current | 2.6 A 16 kHz |
| Output Current 3S Peak | 7.8 A 220 V |
| Continuous Power | 400 W 220 V |
| Nominal Power | 0.4 kW 220 V 16 kHz |
| Switching Frequency | 16 kHz |
| Overvoltage Category | III |
| Maximum Leakage Current | 1.3 mA |
| Output Voltage | <= power supply voltage |
| Electrical Isolation | Between power and control |
| Type Of Cable | Shielded motor cable 32131 °F (055 °C)) copper |
| Electrical Connection | Spring terminal 0.821 mm ² , AWG 18 L1-L2) Spring terminal 0.821 mm ² , AWG 18 R, S, T) Spring terminal 0.821 mm ² , AWG 18 U, V, W, PE) Spring terminal 0.821 mm ² , AWG 18 PA/+, PBe) |
| Discrete Input Number | 8 programmable CN1) 1 pulse train input (PTI) CN1) 2 fast capture CN1) 1 safety function STO CN9) |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Disorato Input Voltago | |
|--|---|
| Discrete Input Voltage | 24 V DC logic |
| Discrete Input Logic | Positive or negative CN1) |
| Discrete Output Number | 5 logic output CN1)1224 V DC 1 pulse train output (PTO) CN1) |
| Discrete Output Voltage | 1224 V DC |
| Discrete Output Logic | Positive or negative CN1) |
| Analogue Input Number | 2 |
| Absolute Accuracy Error | 0.1 % |
| Analogue Input Type | V_REF voltage analog input - 1010 V 10 kOhm 14 bits T_REF voltage analog input |
| Control Signal Type | Servo motor encoder feedback CN2 |
| Protection Type | Against reverse polarity inputs signal Against short-circuits outputs signal Overcurrent motor Overvoltage motor Undervoltage motor Overheating motor Overload motor Overspeed motor |
| Safety Function | STO (safe torque off), Integrated |
| Safety Level | SIL 2 IEC 61800-5-2 2007 SIL 2 IEC 61508-1 2010 PL d/category 3 ISO 13849-1 2008 SIL 2 ISO 13849-1 2009/AC SIL 2 IEC 60204-1 2006 SIL 2 IEC 60204-1 2009/A1 SIL 2 IEC 60204-1 2010/AC SIL 2 IEC 62061 2012 |
| | |
| Communication Interface | CANopen, Integrated CANmotion, Integrated |
| Communication Interface | |
| | CANmotion, Integrated |
| Connector Type | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion |
| Connector Type Method Of Access | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion |
| Connector Type Method Of Access Transmission Rate | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion |
| Connector Type Method Of Access Transmission Rate Number Of Addresses | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led Signalling Function | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CSA |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led Signalling Function Marking | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Red) charge 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CE CULus |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led Signalling Function Marking Type Of Cooling | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CE CULus Natural convection |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led Signalling Function Marking Type Of Cooling Operating Position | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CE CULus Natural convection Vertical Servo motor BCH2 2.36 in (60 mm), 2 400 W Servo motor BCH2 3.15 in (80 mm), 1 400 W |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led Signalling Function Marking Type Of Cooling Operating Position Product Compatibility | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Red) cror Servo status and fault codes five 7-segment display units CSA CE CULus Natural convection Vertical Servo motor BCH2 2.36 in (60 mm), 2 400 W Servo motor BCH2 5.12 in (130 mm), 1 300 W |
| Connector Type Method Of Access Transmission Rate Number Of Addresses Physical Interface Status Led Signalling Function Marking Type Of Cooling Operating Position Product Compatibility Width | CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.21 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.12328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.12 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Red) charge 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CE CULus Natural convection Vertical Servo motor BCH2 2.36 in (60 mm), 2 400 W Servo motor BCH2 5.12 in (130 mm), 1 400 W Servo motor BCH2 5.12 in (130 mm), 1 300 W 2.17 in (55 mm) |

| Output Current 3S Peak 2 | 7.8 A 220 V |
|--------------------------|-------------|
| Output Current 3S Peak 3 | 7.8 A 220 V |

Environment

| Electromagnetic Compatibility | Conducted emission - test level: level 3 category C3 conforming to IEC 61800-3 |
|--|---|
| Standards | IEC 61800-5-1 |
| Product Certifications | cULus CSA CE |
| Ip Degree Of Protection | IP20 |
| Vibration Resistance | 3M4 3 mm 9200 Hz)IEC 60721-3-3 |
| Shock Resistance | 10 gn, type I IEC 60721-3-3 |
| Relative Humidity | 595 % without condensation |
| Ambient Air Temperature For Operation | 32131 °F (055 °C) |
| Ambient Air Temperature For Storage | -13149 °F (-2565 °C) |
| Operating Altitude | <= 3280.84 ft (1000 m) without derating > 3280.846561.68 ft (> 10002000 m) 1 % per 100 m |

Ordering and shipping details

| Category | US1PC5118262 |
|-------------------|---------------|
| Discount Schedule | PC51 |
| Gtin | 3606480711787 |
| Returnability | Yes |
| Country Of Origin | CN |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.99 in (7.594 cm) |
| Package 1 Width | 9.06 in (23.001 cm) |
| Package 1 Length | 9.28 in (23.564 cm) |
| Package 1 Weight | 2.89 lb(US) (1.31 kg) |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 5 |
| Package 2 Height | 11.81 in (30 cm) |
| Package 2 Width | 11.77 in (29.9 cm) |
| Package 2 Length | 15.67 in (39.8 cm) |
| Package 2 Weight | 15.90 lb(US) (7.211 kg) |
| Unit Type Of Package 3 | P06 |
| Number Of Units In Package 3 | 40 |
| Package 3 Height | 31.50 in (80 cm) |
| Package 3 Width | 31.50 in (80 cm) |
| Package 3 Length | 23.62 in (60 cm) |

Package 3 Weight

147.54 lb(US) (66.924 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards


| REACh Declaration |
|---|
| Pro-active compliance (Product out of EU RoHS legal scope) |
| China RoHS declaration |
| Product Environmental Profile |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| End of Life Information |
| WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| |

Product data sheet

Dimensions Drawings

Dimensions

Dimensions of Drive



Product data sheet

Mounting and Clearance

Mounting Clearance

Mounting Distances and Air Circulation

