Product data sheet

Specifications





Miniature circuit breaker (MCB), Multi9 C60H, 2P, 25A, C curve, 15kA (IEC/EN 60947-2)

M9F14225

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 269.00 USD

Main

Range Multi9 Product Name Multi9 C60 Product Or Component Type Miniature circuit-breaker Device Short Name C60H Device Application Distribution Poles Description 2P Number Of Protected Poles 2 Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA Icu <= 125 V DC EN/IEC 60947-2 30 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Product Certifications EAC CCC		
Product Or Component Type Miniature circuit-breaker Device Short Name C60H Device Application Distribution Poles Description 2P Number Of Protected Poles 2 Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA Icu <= 125 V DC EN/IEC 60947-2 30 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Product Certifications EAC	Range	Multi9
Device Short Name C60H Device Application Distribution Poles Description 2P Number Of Protected Poles 2 Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA Icu <= 125 V DC EN/IEC 60947-2 30 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Product Certifications EAC	Product Name	Multi9 C60
Device Application Distribution Poles Description 2P Number Of Protected Poles 2 Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA Icu <= 125 V DC EN/IEC 60947-2 30 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Product Or Component Type	Miniature circuit-breaker
Poles Description 2P Number Of Protected Poles 2 Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA lcu <= 125 V DC EN/IEC 60947-2 30 kA lcu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA lcu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA lcu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Device Short Name	С60Н
Number Of Protected Poles 2 Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA Icu <= 125 V DC EN/IEC 60947-2 30 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Device Application	Distribution
Line Rated Current 25 A 122 °F (50 °C) EN/IEC 60947-2 Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA Icu <= 125 V DC EN/IEC 60947-2 30 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Poles Description	2P
Network Type DC AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA lcu <= 125 V DC EN/IEC 60947-2 30 kA lcu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA lcu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA lcu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Number Of Protected Poles	2
AC Trip Unit Technology Thermal-magnetic Curve Code C Breaking Capacity 25 kA lcu <= 125 V DC EN/IEC 60947-2 30 kA lcu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA lcu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA lcu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Line Rated Current	25 A 122 °F (50 °C) EN/IEC 60947-2
Curve Code C Breaking Capacity 25 kA lcu <= 125 V DC EN/IEC 60947-2 30 kA lcu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA lcu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA lcu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Network Type	
Breaking Capacity 25 kA lcu <= 125 V DC EN/IEC 60947-2	Trip Unit Technology	Thermal-magnetic
30 kA lcu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA lcu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 10 kA lcu 440 V AC 50/60 Hz between phases EN/IEC 60947-2 Utilisation Category Category A EN/IEC 60947-2 Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Curve Code	С
Suitability For Isolation Yes EN/IEC 60947-2 Standards EN/IEC 60947-2 Product Certifications EAC	Breaking Capacity	30 kA lcu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 15 kA lcu 415 V AC 50/60 Hz between phases EN/IEC 60947-2
Standards EN/IEC 60947-2 Product Certifications EAC	Utilisation Category	Category A EN/IEC 60947-2
Product Certifications EAC	Suitability For Isolation	Yes EN/IEC 60947-2
20	Standards	EN/IEC 60947-2
	Product Certifications	

Complementary

Network Frequency	50/60 Hz	
[Ue] Rated Operational Voltage	240 V AC 50/60 Hz between phases	
	415 V AC 50/60 Hz between phases	
	440 V AC 50/60 Hz between phases	
	<= 125 V DC	
Magnetic Tripping Limit	8.5 x ln +/- 20 % AC	
	12 x ln +/- 20 % DC	
[Ics] Rated Service Breaking	15 kA 50 % EN/IEC 60947-2 - 240 V AC 50/60 Hz	
Capacity	7.5 kA 50 % EN/IEC 60947-2 - 415 V AC 50/60 Hz	
	5 kA 50 % EN/IEC 60947-2 - 440 V AC 50/60 Hz	
	25 kA 100 % EN/IEC 60947-2 - <= 125 V DC	
[Ui] Rated Insulation Voltage	500 V AC 50/60 Hz EN/IEC 60947-2	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Uimp] Rated Impulse Withstand Voltage	6 KVEN/IEC 60947-2
Contact Position Indicator	Yes
Control Type	Toggle
Local Signalling	ON/OFF indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 Mm Pitches	4
Height	3.19 in (81 mm)
Width	1.42 in (36 mm)
Depth	2.83 in (72 mm)
Net Weight	0.53 lb(US) (0.24 kg)
Color	Gray
Mechanical Durability	20000 cycles
Electrical Durability	10000 cycles
Provision For Padlocking	Padlockable
Connections - Terminals	Tunnel type terminal top or bottom) 0.000.04 in² (125 mm²) - rigid Tunnel type terminal top or bottom) 0.000.04 in² (125 mm²) - flexible Tunnel type terminal top or bottom) 0.000.04 in² (125 mm²) - flexible with ferrule
Wire Stripping Length	0.55 in (14 mm) for top or bottom connection
Tightening Torque	17.70 lbf.in (2 N.m) top or bottom
Earth-Leakage Protection	Separate block

Environment

Heat Dissipation	6.2 W 415 V - 25 A
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution Degree	3 EN/IEC 60947-2
Overvoltage Category	IV
Tropicalisation	2 IEC 60068-1
Relative Humidity	95 % 131 °F (55 °C)
Ambient Air Temperature For Operation	-22158 °F (-3070 °C)
Ambient Air Temperature For Storage	-40176 °F (-4080 °C)

Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
Gtin	3606480577215
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1

PCE

Number Of Units In Package 1	1
Package 1 Height	1.42 in (3.6 cm)
Package 1 Width	2.95 in (7.5 cm)
Package 1 Length	3.35 in (8.5 cm)
Package 1 Weight	7.94 oz (225 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	6
Package 2 Height	3.07 in (7.8 cm)
Package 2 Width	3.39 in (8.6 cm)
Package 2 Length	8.86 in (22.5 cm)
Package 2 Weight	3.08 lb(US) (1.397 kg)
Unit Type Of Package 3	S03
Number Of Units In Package 3	36
Package 3 Height	11.81 in (30 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	19.56 lb(US) (8.871 kg)

Package 3 Weight

19.56 lb(US) (8.871 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Plastic Parts & Cables Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations