

Product data sheet

Specifications



Multi9 - auxiliary contact - 1 OF - 1NO/NC - 24...415 V AC - 24...130 V DC

MGN26924

 **Discontinued on:** Feb 17, 2021

 **Discontinued**

Main

Range Of Product	Acti9
Product Or Component Type	OC contact
Device Short Name	OF
Signal Contacts Composition	1 NO/NC
Line Rated Current	3 A at 415 V, AC 50/60 Hz 6 A at <= 240 V, AC 50/60 Hz
[Uc] Control Circuit Voltage	24...130 V DC 24...415 V AC 50/60 Hz
9 Mm Pitches	1

Complementary

Mounting Mode	Clip-on
Mounting Support	DIN rail
Height	3.35 in (85 mm)
Width	0.35 in (9 mm)
Depth	2.89 in (73.5 mm)
Net Weight	1.06 oz (30 g)
Color	White
Connections - Terminals	Clamp terminal bottom) 2 0.00 in² (1.5 mm²) - flexible Clamp terminal bottom) 1 0.00...0.00 in² (0.5...2.5 mm²) - rigid Clamp terminal bottom) 2 0.00 in² (1.5 mm²) - flexible with ferrule
Wire Stripping Length	0.35 in (9 mm) for bottom connection
Tightening Torque	8.85 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-5-1
Ambient Air Temperature For Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature For Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Gtin	3606480545160
------	---------------

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.87 in (2.2 cm)
Package 1 Width	3.15 in (8 cm)
Package 1 Length	3.70 in (9.4 cm)
Package 1 Weight	1.34 oz (38 g)

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration	Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	