Product data sheet





Multi 9 - C60 UL489 - MCB - 3P -2 A - C Curve - 480Y/277 V - 10 kA - tunnel ter

MGN61324

Discontinued on: Jul 12, 2021



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Range | Multi9 |
|---------------------------|--|
| Product Name | Multi9 C60 |
| Product Or Component Type | Miniature circuit-breaker |
| Device Short Name | C60 UL489 |
| Device Application | Distribution |
| Poles Description | 3P |
| Number Of Protected Poles | 3 |
| Line Rated Current | 2 A 77 °F (25 °C) |
| Network Type | AC |
| Trip Unit Technology | Thermal-magnetic |
| Curve Code | С |
| Breaking Capacity | 10 kA AIR 480Y/277 V AC UL 489 10 kA AIR 480Y/277 V AC CSA C22.2 No 5.2 10 kA Icu 480Y/277 V AC EN/IEC 60947-2 10 kA Icu 480Y/277 V AC GB 14048.2 |
| Suitability For Isolation | Yes EN/IEC 60947-2 |

Complementary

| Network Frequency | 50/60 Hz |
|--|-------------------------|
| [Ue] Rated Operational Voltage | 480Y/277 V AC |
| Magnetic Tripping Limit | 8.5 x In +/- 20 % AC |
| Limitation Class | 3 EN/IEC 60947-2 |
| [Ui] Rated Insulation Voltage | 500 V AC EN/IEC 60947-2 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kVEN/IEC 60947-2 |
| Contact Position Indicator | Yes |
| Control Type | Toggle |
| Local Signalling | ON/OFF indication |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| 9 Mm Pitches | 6 |
| Height | 5.55 in (141 mm) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Width | 2.13 in (54 mm) |
|--------------------------|--|
| Depth | 2.70 in (68.7 mm) |
| Net Weight | 0.73 lb(US) (0.33 kg) |
| Color | Gray |
| Mechanical Durability | 20000 cycles |
| Electrical Durability | 10000 cycles |
| Provision For Padlocking | Padlockable |
| Connections - Terminals | Tunnel type terminal top or bottom) - 1 0.000.00 in² (11.5 mm²) AWG 18AWG 16) - rigid Tunnel type terminal top or bottom) - 2 0.000.00 in² (11.5 mm²) AWG 18AWG 16) - rigid |
| Tightening Torque | 7.08 lbf.in (0.8 N.m) top or bottom |

Environment

| Standards | GB 14048.2 |
|---------------------------------------|--|
| | EN/IEC 60947-2 |
| | UL 489 |
| | CSA C22.2 No 5 |
| Product Certifications | CSA |
| | CCC |
| | IEC |
| | UL |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
| | IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution Degree | 3 EN/IEC 60947-2 |
| Overvoltage Category | IV |
| Tropicalisation | 2 IEC 60068-1 |
| Relative Humidity | 95 % 131 °F (55 °C) |
| Operating Altitude | 6561.68 ft (2000 m) |
| Ambient Air Temperature For Operation | -22158 °F (-3070 °C) |
| Ambient Air Temperature For Storage | -40176 °F (-4080 °C) |

Ordering and shipping details

| Category | US10DE200915 |
|-------------------|--------------|
| Discount Schedule | 0DE2 |
| Gtin | 785901809944 |
| Returnability | No |
| Country Of Origin | US |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.20 in (5.6 cm) |
| Package 1 Width | 2.95 in (7.5 cm) |
| Package 1 Length | 5.71 in (14.5 cm) |
| Package 1 Weight | 17.35 oz (492 g) |

Contractual warranty

Warranty

Apr 23, 2024

18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

| ⊘ | Mercury Free | |
|----------|----------------------------|-----|
| ⊘ | Rohs Exemption Information | Yes |
| ⊘ | Halogen Free Product | |

Certifications & Standards

| Eu Rohs Directive | Compliant |
|-----------------------|--|
| | EU RoHS Declaration |
| | |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information. |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |