# **Product data sheet**





Multi9 - C60 UL489 - MCB - 3P - 5 A - D Curve - 480Y/277 V - 10 kA tunnel ter

MGN61360

Discontinued on: Jun 30, 2021

(!) Discontinued

#### Main

| Range                     | Multi9   |  |
|---------------------------|--|--|
| Product Name              | Multi9 C60   |  |
| Product Or Component Type | Miniature circuit-breaker  |  |
| Device Short Name         | C60 UL489  |  |
| Device Application        | Distribution   |  |
| Poles Description         | 3P   |  |
| Number Of Protected Poles | 3  |  |
| Line Rated Current        | 5 A 77 °F (25 °C)  |  |
| Network Type              | AC   |  |
| Trip Unit Technology      | Thermal-magnetic   |  |
| Curve Code                | D  |  |
| Breaking Capacity         | 10 kA AIR 480Y/277 V AC UL 489<br>10 kA AIR 480Y/277 V AC CSA C22.2 No 5.2<br>10 kA Icu 480Y/277 V AC EN/IEC 60947-2<br>10 kA Icu 480Y/277 V AC GB 14048.2 |  |
| Suitability For Isolation | Yes EN/IEC 60947-2   |  |

### Complementary

| Network Frequency                      | 50/60 Hz                |
|--|-------------------------|
| [Ue] Rated Operational Voltage         | 480Y/277 V AC           |
| Magnetic Tripping Limit                | 12 x In +/- 20 % AC     |
| Limitation Class                       | 3 EN/IEC 60947-2        |
| [Ui] Rated Insulation Voltage          | 500 V AC EN/IEC 60947-2 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kVEN/IEC 60947-2      |
| Contact Position Indicator             | Yes                     |
| Control Type                           | Toggle                  |
| Local Signalling                       | ON/OFF indication       |
| Mounting Mode                          | Clip-on                 |
| Mounting Support                       | DIN rail                |
| 9 Mm Pitches                           | 6                       |
| Height                                 | 5.55 in (141 mm)        |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Width                    | 2.13 in (54 mm)  |
|--------------------------|--|
| Depth                    | 2.70 in (68.7 mm)  |
| Net Weight               | 0.73 lb(US) (0.33 kg)  |
| Color                    | Gray   |
| Mechanical Durability    | 20000 cycles   |
| Electrical Durability    | 10000 cycles   |
| Provision For Padlocking | Padlockable  |
| Connections - Terminals  | Tunnel type terminal top or bottom) - 1 0.000.00 in² (11.5 mm²) AWG 18AWG 16) - rigid  Tunnel type terminal top or bottom) - 2 0.000.00 in² (11.5 mm²) AWG 18AWG 16) - rigid |
| Tightening Torque        | 7.08 lbf.in (0.8 N.m) top or bottom  |

### **Environment**

| Standards                             | GB 14048.2<br>EN/IEC 60947-2<br>UL 489<br>CSA C22.2 No 5                      |
|---------------------------------------|---|
| Product Certifications                | CSA<br>CCC<br>IEC<br>UL   |
| Ip Degree Of Protection               | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution Degree                      | 3 EN/IEC 60947-2  |
| Overvoltage Category                  | IV  |
| Tropicalisation                       | 2 IEC 60068-1   |
| Relative Humidity                     | 95 % 131 °F (55 °C)   |
| Operating Altitude                    | 6561.68 ft (2000 m)   |
| Ambient Air Temperature For Operation | -22158 °F (-3070 °C)  |
| Ambient Air Temperature For Storage   | -40176 °F (-4080 °C)  |

## Ordering and shipping details

| Category          | 00915-C60N MINIATURE CIRCUIT BREAKER-UL489 |
|-------------------|--|
| Discount Schedule | DE2  |
| Gtin              | 785901489030                               |
| Returnability     | No   |
| Country Of Origin | FR   |

## **Packing Units**

| Unit Type Of Package 1       | PCE                  |
|------------------------------|----------------------|
| Number Of Units In Package 1 | 1                    |
| Package 1 Height             | 2.30 in (5.842 cm)   |
| Package 1 Width              | 3.00 in (7.62 cm)    |
| Package 1 Length             | 5.60 in (14.224 cm)  |
| Package 1 Weight             | 16.80 oz (476.272 g) |

## **Contractual warranty**

Warranty

Apr 25, 2024

18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

#### Well-being performance

| <b>②</b> | Mercury Free               |     |
|----------|----------------------------|-----|
| <b>⊘</b> | Rohs Exemption Information | Yes |
| <b>⊘</b> | Halogen Free Product       |     |

#### **Certifications & Standards**

| Eu Rohs Directive     | Compliant  |
|-----------------------|--|
|                       | EU RoHS Declaration  |
| China Rohs Regulation | China RoHS declaration   |
|                       | Product out of China RoHS scope. Substance declaration for your information.   |
| Weee                  | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |