# Product data sheet

Specifications





### Multi9 - C60 UL489 - MCB - 1P - 5 A - C Curve - 277 V - 10 kA - ring term

MGN61371

() Discontinued on: Feb 17, 2021

Main

| mann                      |  |
|---------------------------|--|
| Range                     | Multi9   |
| Product Name              | Multi9 C60   |
| Product Or Component Type | Miniature circuit-breaker  |
| Device Short Name         | C60 UL489  |
| Device Application        | Distribution   |
| Poles Description         | 1P   |
| Number Of Protected Poles | 1  |
| Line Rated Current        | 5 A 77 °F (25 °C)  |
| Network Type              | AC   |
| Trip Unit Technology      | Thermal-magnetic   |
| Curve Code                | С  |
| Breaking Capacity         | 10 kA AIR 277 V AC UL 489<br>10 kA AIR 277 V AC CSA C22.2 No 5.2<br>10 kA Icu 277 V AC EN/IEC 60947-2<br>10 kA Icu 277 V AC GB 14048.2 |
| Suitability For Isolation | Yes EN/IEC 60947-2   |

#### Complementary

| Network Frequency                         | 50/60 Hz                |
|---|-------------------------|
| [Ue] Rated Operational Voltage            | 277 V AC                |
| Magnetic Tripping Limit                   | 8.5 x ln +/- 20 % AC    |
| Limitation Class                          | 3 EN/IEC 60947-2        |
| [Ui] Rated Insulation Voltage             | 500 V AC EN/IEC 60947-2 |
| [Uimp] Rated Impulse Withstand<br>Voltage | 6 kVEN/IEC 60947-2      |
| Contact Position Indicator                | Yes                     |
| Control Type                              | Toggle                  |
| Local Signalling                          | ON/OFF indication       |
| Mounting Mode                             | Clip-on                 |
| Mounting Support                          | DIN rail                |
| 9 Mm Pitches                              | 2                       |
| Height                                    | 5.55 in (141 mm)        |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Width                    | 0.71 in (18 mm)                    |
|--------------------------|------------------------------------|
| Depth                    | 2.70 in (68.7 mm)                  |
| Net Weight               | 0.24 lb(US) (0.11 kg)              |
| Color                    | Gray                               |
| Mechanical Durability    | 20000 cycles                       |
| Electrical Durability    | 10000 cycles                       |
| Provision For Padlocking | Padlockable                        |
| Connections - Terminals  | Ring terminal top or bottom)       |
| Tightening Torque        | 17.70 lbf.in (2 N.m) top or bottom |

#### Environment

| Standards                                | GB 14048.2<br>EN/IEC 60947-2   |
|--|--|
|  | UL 489<br>CSA C22.2 No 5   |
| Product Certifications                   | CSA<br>CCC<br>IEC<br>UL  |
| Ip Degree Of Protection                  | IP40 (modular enclosure) conforming to IEC 60529<br>IP10 conforming to IEC 60529 |
| Pollution Degree                         | 3 EN/IEC 60947-2   |
| Overvoltage Category                     | IV   |
| Tropicalisation                          | 2 IEC 60068-1  |
| Relative Humidity                        | 95 % 131 °F (55 °C)  |
| Operating Altitude                       | 6561.68 ft (2000 m)  |
| Ambient Air Temperature For<br>Operation | -22158 °F (-3070 °C)   |
| Ambient Air Temperature For<br>Storage   | -40176 °F (-4080 °C)   |

# Ordering and shipping details

| Category          | 00915-C60N MINIATURE CIRCUIT BREAKER-UL489 |
|-------------------|--|
| Discount Schedule | DE2  |
| Gtin              | 785901475460                               |
| Returnability     | No   |
| Country Of Origin | FR   |

#### **Packing Units**

| U                            |                     |
|------------------------------|---------------------|
| Unit Type Of Package 1       | PCE                 |
| Number Of Units In Package 1 | 1                   |
| Package 1 Height             | 2.95 in (7.501 cm)  |
| Package 1 Width              | 0.71 in (1.801 cm)  |
| Package 1 Length             | 5.55 in (14.1 cm)   |
| Package 1 Weight             | 5.76 oz (163.293 g) |

# **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

#### **Certifications & Standards**

| Eu Rohs Directive     | Compliant  |
|-----------------------|--|
|                       | EU RoHS Declaration  |
| China Rohs Regulation | China RoHS declaration   |
|                       | Product out of China RoHS scope. Substance declaration for your information.   |
| Weee                  | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |