Product data sheet

Specifications





① Discontinued - Service only

servo motor MH3 140 11,1Nm,key,multi,brake,IP65/ IP67,3kRPM

MH31401P12F2200

() Discontinued on: Sep 30, 2023

() To be end-of-service on: Mar 31, 2025

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	PacDrive 3	
Product Or Component Type	AC servo motors	
Device Short Name	MH3	

Complementary

Complementary	
Maximum Mechanical Speed	4000 rpm
[Us] Rated Supply Voltage	115480 V
Phase	Three phase
Continuous Stall Current	8.58 A
Continuous Stall Torque	91.16 lbf.in (10.3 N.m), 115480 V, three phase
Continuous Power	2640 W
Peak Stall Torque	353.14 lbf.in (39.9 N.m), 115480 V, three phase
Nominal Output Power	0.98 W, 115 V 1.78 W, 230 V 2.64 W, 400 V 2.64 W, 480 V
Nominal Torque	82.84 lbf.in (9.36 N.m) LXM52 7.82 mA, 115 V, 1 phase 75.23 lbf.in (8.5 N.m) LXM52 7.3 mA, 230 V, 1 phase 63.90 lbf.in (7.22 N.m) LXM52 6.35 mA, 400 V, 3 phase 63.90 lbf.in (7.22 N.m) LXM52 6.35 mA, 480 V, 3 phase 82.84 lbf.in (9.36 N.m) LXM62 7.82 mA, 115 V, 1 phase 75.23 lbf.in (8.5 N.m) LXM62 7.3 mA, 230 V, 1 phase 63.90 lbf.in (7.22 N.m) LXM62 6.35 mA, 400 V, 3 phase 63.90 lbf.in (7.22 N.m) LXM62 6.35 mA, 480 V, 3 phase
Nominal Speed	1000 rpm LXM52 7.82 mA, 115 V, 1 phase 2000 rpm LXM52 7.3 mA, 230 V, 1 phase 3500 rpm LXM52 6.35 mA, 400 V, 3 phase 3500 rpm LXM52 6.35 mA, 480 V, 3 phase 1000 rpm LXM62 7.82 mA, 115 V, 1 phase 2000 rpm LXM62 7.3 mA, 230 V, 1 phase 3500 rpm LXM62 6.35 mA, 400 V, 3 phase 3500 rpm LXM62 6.35 mA, 480 V, 3 phase
Maximum Current Irms	29.8 A
Shaft End	Parallel key
Second Shaft	Without second shaft end
Shaft Diameter	0.94 in (24 mm)
Shaft Length	1.97 in (50 mm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Key Width	0.31 in (8 mm)	
Ip Degree Of Protection	IP65 standard	
Encoder Type	Multiturn SinCos Hiperface	
Speed Feedback Resolution	128 periods	
Holding Brake	With	
Holding Torque	159.31 lbf.in (18 N.m)	
Mounting Support	International standard flange	
Motor Flange Size	5.51 in (140 mm)	
Electrical Connection	Rotatable right-angled connectors	
Torque Constant	1.2 N.m/A 248 °F (120 °C)	
Back Emf Constant	77.41 V/krpm	
Number Of Motor Poles	10	
Rotor Inertia	17.96 kg.cm ²	
Stator Resistance	0.69 Ohm	
Stator Inductance	6.72 mH	
Stator Electrical Time Constant	9.7 ms	
Maximum Radial Force Fr	1930 N 1000 rpm 1530 N 2000 rpm	
	1340 N 3000 rpm	
Brake Pull-In Power	18 W	
Type Of Cooling	Natural convection	
Length	7.36 in (187 mm)	
Centring Collar Diameter	5.12 in (130 mm)	
Centring Collar Depth	0.14 in (3.5 mm)	
Number Of Mounting Holes	4	
Mounting Holes Diameter	0.43 in (11 mm)	
Circle Diameter Of The Mounting Holes	6.50 in (165 mm)	
Net Weight	22.71 lb(US) (10.3 kg)	

Ordering and shipping details

Category	US1PC5218359	
Discount Schedule	PC52	
Gtin	3606485396927	
Returnability	No	
Country Of Origin	US	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	10.24 in (26.0 cm)	
Package 1 Width	7.87 in (20.0 cm)	
Package 1 Length	23.23 in (59.0 cm)	

Package 1 Weight

20.50 lb(US) (9.3 kg)

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov