



Panelboard interior, NF, main lugs, 400A, Al bus, 54 pole spaces, 3 phase, 4 wire, 600Y/347 VAC max

NF454L4

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 2,901.00 USD

#### Main

| Panelboard Type             | Main lugs   |
|-----------------------------|-------------|
| Branch Circuit Breaker Type | EDB/EDG/EDJ |
| Busbar Material             | Aluminium   |

### Complementary

| Number Of Spaces               | 54  |
|--------------------------------|---|
| Enclosure Nominal Height       | 56 in (1422.40 mm)  |
| Enclosure Nominal Width        | 20 in (508.00 mm)   |
| Enclosure Nominal Depth        | 5.75 in (146.05 mm) NEMA 1<br>6.5 in (165.10 mm) NEMA 3R/5/12   |
| Line Rated Current             | 400 A   |
| [lu] Rated Interrupted Current | 65 kA   |
| Wiring Configuration           | 4-wire  |
| Number Of Phases               | 3 phase   |
| Voltage Rating                 | 600Y/347 V AC   |
| Connections - Terminals        | Lug line AWG 1/0750 kcmil aluminium<br>Lug neutral AWG 1/0750 kcmil aluminium   |
| Tightening Torque              | 274.99300.04 lbf.in (31.0733.90 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 274.99300.04 lbf.in (31.0733.90 N.m) 0.080.27 in² (53.48177.3 mm²) (AWG 1/0350 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.24 in² (53.48152 mm²) (AWG 1/0300 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.24 in² (53.48152 mm²) (AWG 1/0300 kcmil) |
| Height                         | 58 in (1473.20 mm)  |
|                                | 10.44 in (265.18 mm)  |

#### **Environment**

| Standards    | UL 67     |  |
|--------------|-----------|--|
| o tarradi do |           |  |
|              | CSA C22 2 |  |

## Ordering and shipping details

| Category          | US1PE1A08350 |
|-------------------|--------------|
| Discount Schedule | PE1A         |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Gtin              | 785901940050 |
|-------------------|--------------|
| Returnability     | No           |
| Country Of Origin | MX           |

# **Packing Units**

| Unit Type Of Package 1       | PCE                      |
|------------------------------|--------------------------|
| Number Of Units In Package 1 | 1                        |
| Package 1 Height             | 6.18 in (15.7 cm)        |
| Package 1 Width              | 14.21 in (36.1 cm)       |
| Package 1 Length             | 58.39 in (148.3 cm)      |
| Package 1 Weight             | 30.00 lb(US) (13.608 kg) |

## **Contractual warranty**

Warranty 18 months

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

| Reach Free Of Svhc         |   |
|----------------------------|---|
| Toxic Heavy Metal Free     |   |
| Mercury Free               |   |
| Rohs Exemption Information | Yes   |
|                            |   |
| Reach Regulation           | REACh Declaration   |
| Eu Rohs Directive          | Compliant   |
|                            | EU RoHS Declaration   |
| China Rohs Regulation      | China RoHS declaration  |
| California Proposition 65  | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |