Specifications





External handle with 405 barrel & key

NSYTHL405PLM

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 10.51 USD

Main

Range	Thalassa
Accessory / Separate Part Category	Locking accessory
Product Or Component Type	Handle
Application	Multi-purpose
Mounting Support	Direct mounting on door
Product Compatibility	PLM with Height ≤ 847mm
Range Compatibility	Thalassa Thalassa PLM
Device Composition	1 cylindrical barrel 2 key 1 handle with key lock

Complementary

Quantity Per Set	Set of 1
Lock Type	Key lock
Type Of Keylock	Cylinder
Key Number	405

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
Gtin	3606480192821
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.18 in (3.0 cm)
Package 1 Width	3.54 in (9.0 cm)
Package 1 Length	5.12 in (13.0 cm)
Package 1 Weight	2.50 oz (71.0 g)

Contractual warranty

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations