

Product data sheet

Specifications



off-delay timing relay - 1 s..100 h - 24..240 V AC - 1 contact

RE88865135

 **Discontinued on:** Jan 29, 2021

 **Discontinued**

Main

Range Of Product	Zelio Time
Product Or Component Type	Industrial timing relay
Contacts Type And Composition	1 C/O timed contact, AgNi (cadmium free)
Component Name	RE88865
Time Delay Type	C
Time Delay Range	10 h 1 s 10 min 1 h 1 min 10 s 100 h

Complementary

Discrete Output Type	Relay
Width Pitch Dimension	0.89 in (22.5 mm)
[Us] Rated Supply Voltage	24 V DC 24...240 V AC 50/60 Hz
Voltage Range	0.85...1.1 Us
Connections - Terminals	Screw terminals, 2 x 1.5 mm ² with cable end Screw terminals, 2 x 2.5 mm ² without cable end
Housing Material	Self-extinguishing
Repeat Accuracy	+/- 0.5 % IEC 61812-1
Temperature Drift	+/- 0.05 %/°C
Voltage Drift	+/- 0.2 %/V
Setting Accuracy Of Time Delay	+/- 10 % of full scale 25 °C IEC 61812-1
Minimum Pulse Duration	100 ms under load 30 ms
Maximum Reset Time	100 ms on de-energisation
On-Load Factor	100 %
Maximum Power Consumption	32 VA 240 V
Maximum Power Consumption	0.6 W 24 V 1.5 W 240 V
Breaking Capacity	2000 VA
Breaking Capacity	80 W

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Minimum Switching Current	10 mA
Maximum Switching Current	8 A
Maximum Switching Voltage	250 V
Electrical Durability	100000 cycles 8 A, 250 V resistive
Mechanical Durability	5000000 cycles
[Uimp] Rated Impulse Withstand Voltage	5 kV 1.2...50 µs IEC 60664-1 5 kV 1.2...50 µs IEC 61812-1
Marking	CE
Creepage Distance	4 kV/3 IEC 60664-1
Surge Withstand	1 kV differential mode IEC 61000-4-5 level 3 2 kV common mode IEC 61000-4-5 level 3
Mounting Support	35 mm symmetrical mounting rail conforming to EN 50022
Local Signalling	for flashing: timing in progress LED indicator (green) for on steady: relay energised, no timing in progress LED indicator (green) for pulsing: relay energised, no timing in progress LED indicator (green)
Net Weight	0.20 lb(US) (0.09 kg)

Environment

Immunity To Microbreaks	10 ms
Dielectric Strength	2.5 kV 1 mA/1 minute 50 Hz IEC 61812-1
Standards	93/68/EEC IEC 60669-2-3 89/336/EEC IEC 61812-1 73/23/EEC EN 50081-1/2 EN 50082-1/2
Product Certifications	GL cULus CSA
Ambient Air Temperature For Operation	-4...140 °F (-20...60 °C)
Ambient Air Temperature For Storage	-22...140 °F (-30...60 °C)
Ip Degree Of Protection	IP20 IEC 60529 terminal block) IP40 IEC 60529 housing) IP50 IEC 60529 front face)
Vibration Resistance	0.35 mm 10...55 Hz)IEC 60068-2-6
Relative Humidity	93 % without condensation IEC 60068-2-3
Resistance To Electrostatic Discharge	6 kV in contact EN/IEC 61000-4-2 level 3 8 kV in air EN/IEC 61000-4-2 level 3
Resistance To Electromagnetic Fields	9.14 V/m (10 V/m) 80 MHz to 1 GHz ENV 50140/204 level 3 9.14 V/m (10 V/m) 80 MHz to 1 GHz IEC 61000-4-3 level 3
Resistance To Fast Transients	1 kV IEC 61000-4-4 level 3 capacitive connecting clip) 2 kV IEC 61000-4-4 level 3 direct)
Immunity To Radioelectric Fields	10 V 0.15...80 MHz)ENV 50141 (IEC 61000-4-6)
Immunity To Voltage Dips	30 % / 10 ms IEC 61000-4-11 60 % / 100 ms IEC 61000-4-11 95 % / 5 s IEC 61000-4-11
Disturbance Radiated/Conducted	Class B EN 55022 (EN 55011 group 1)

Ordering and shipping details


Category	22370-RE, RM MISC TIMERS & COUNTERS
Discount Schedule	CP2
Gtin	00785901573661
Returnability	No
Country Of Origin	FR

Contractual warranty

Warranty	18 months
----------	-----------


Dimensions Drawings

Width 22.5 mm



Connections and Schema

Wiring Diagram




Technical Description

Function C : Off-Delay Relay with Control Signal


Description

After power-up and closing of the control contact C, the output R closes. When control contact C re-opens, timing T starts. At the end of the timing period, the output(s) R revert(s) to its/their initial state. The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

Legend

-  Relay de-energised
-  Relay energised
-  Output open
-  Output closed

C	Control contact
G	Gate
R	Relay or solid state output
R1/R2	2 timed outputs
R2 inst.	The second output is instantaneous if the right position is selected
T	Timing period
Ta -	Adjustable On-delay
Tr -	Adjustable Off-delay
U	Supply