Product data sheet

Specifications



① To be discontinued

Circuit breaker, PowerPacT R, 2000A, 3 pole, 600VAC, 50kA, busbar, Micrologic 5.0H, 80%, modbus

RLF36200U73AE1

() To be discontinued on: Apr 30, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 36,354.00 USD

Main

Range	PowerPact	
Product Name	PowerPact R	
Product Or Component Type	Circuit breaker	
Device Application	Distribution	

Complementary

2000 A	
3P	
Operating handle	
L	
AIR 125 kA 240 V AC 50/60 Hz UL 489 AIR 100 kA 480 V AC 50/60 Hz UL 489 AIR 50 kA 600 V AC 50/60 Hz UL 489 Icu 125 kA 240 V AC 50/60 Hz IEC 60947-2 Icu 85 kA 380/415 V AC 50/60 Hz IEC 60947-2	
600 V AC 50/60 Hz UL 489	
50/60 Hz	
65 kA 240 V AC 50/60 Hz IEC 60947-2 45 kA 380/415 V AC 50/60 Hz IEC 60947-2	
8 kV IEC 60947-2	
Electronic, harmonic, MicroLogic 5.0 H, LSI	
80 %	
750 V IEC 60947-2	
MicroLogic 5.0 H	
Yes IEC 60947-2	
Category A	
AWG 3/0750 kcmil aluminium/copper	

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Local Signalling	Alarm 1 LED yellow)long-time pick up)	
	1 LED red)long-time pick up)	
	Trip causes 1 LED red)	
	1 LED red)digital ammeter)	
	Phase-loading LED green)load balancing)	
Mounting Mode	Unit mount busbar)	
Mounting Support	Busbar	
Electrical Connection	Busbar connection, line	
	Busbar connection, load	
Terminal Identifier	AL2500RK	
Tightening Torque	601.85 lbf.in (68 N.m) 0.080.62 in² (50400 mm²) (AWG 1/0750 kcmil)	
	601.85 lbf.in (68 N.m) 0.080.23 in² (50150 mm²) (2 x AWG 1/02 x 300 kcmil)	
Number Of Slots	2 auxiliary switch OF plug-in)	
	1 alarm switch SD plug-in)	
	1 voltage release MN or MX plug-in)	
Power Wire Stripping Length	1.38 in (35 mm)	
Height	16.24 in (412.50 mm)	
Width	16.54 in (420.12 mm)	
Depth	14.49 in (368.05 mm)	
Net Weight	52 lb(US) (23.59 kg)	
Quantity Per Set	1	
Communication Interface	Modbus	
Circuit Breaker Application	HACR rated	

Environment

Quality Labels	CE	
Standards	UL	
	CSA	
	NEMA	
	NMX J-266	
	IEC 60947-2	
Product Certifications	UL	
	CSA	
	NOM	
Ip Degree Of Protection	IP40	
Pollution Degree	3 IEC 60947-1	
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)	
Ambient Air Temperature For Storage	-58185 °F (-5085 °C)	
Operating Altitude	< 6561.68 ft (2000 m) without derating	
	13123.36 ft (4000 m) with derating	

Ordering and shipping details

Category	US10DE201245	
Discount Schedule	0DE2	
Returnability	Yes	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Weight

74.00 lb(US) (33.566 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free
Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov