Product data sheet

Specifications





Converter for thermocouples, Harmony Analog, temperature transmitter, 0...150 degree COr 32...302 degree F

RMTJ40BD



Discontinued on: May 19, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Range Of Product | Harmony Analog | |
|---------------------------|--|--|
| Product Or Component Type | Converter for thermocouples | |
| Analogue Input Type | Thermocouple 0150 °C/32302 °F thermocouple J IEC 60584 | |
| Analogue Output Type | Current 020 mA <= 500 Ohm Current 420 mA <= 500 Ohm Voltage 0 10 V >= 100 kOhm | |

Complementary

| Protection Type | Overvoltage protection on output (+/- 30 V) Reverse polarity protection on output Short-circuit protection on output |
|-------------------------------------|--|
| Abnormal Analogue Output Voltage | -1511 V no input or input wire broken 1115 V no input or input wire broken |
| Abnormal Analogue Output Current | -300 mA no input or input wire broken |
| [Us] Rated Supply Voltage | 24 V DC +/- 20 %, non isolated |
| Current Consumption | <= 60 mA current output |
| Local Signalling | for power ON LED (green) |
| Measurement Error | +/- 1 % of full scale 20 °C temporary performance degradation when subject to electromagnetic interference) |
| Repeat Accuracy | +/- 0.25 % full scale 20 °C +/- 0.8 % full scale 60 °C |
| Temperature Coefficient | 200 ppm/°C |
| Cold Junction Compensation | Built-in between 0 and 60 °C |
| Clamping Connection Capacity | 2 x 1.5 mm ² 1 x 2.5 mm ² |
| Tightening Torque | 5.319.74 lbf.in (0.61.1 N.m) |
| Marking | CE |
| Surge Withstand | 0.5 kV 1.2/50 μs IEC 61000-4-5 |
| [Ui] Rated Insulation Voltage | 2 kV |
| Fixing Mode | By screws (mounting plate) Clip-on (35 mm symmetrical DIN rail) |
| Safety Reliability Data | B10d = 45447 MTTFd = 49.2 years |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight 0.26 lb(US) (0.12 kg)

Environment

| Standards | IEC 60947-1 IEC 60584-1 |
|---------------------------------------|--|
| Product Certifications | CSA GL UL |
| Ip Degree Of Protection | IP20 terminal block) IP50 housing) |
| Fire Resistance | 1562 °F (850 °C) IEC 60695-2-1 1562 °F (850 °C) UL |
| Shock Resistance | 50 gn 11 ms IEC 60068-2-27 |
| Vibration Resistance | 5 gn 10100 Hz)IEC 60068-2-6 |
| Resistance To Electrostatic Discharge | 6 kV in contact)IEC 61000-4-2 level 3 8 kV in air)IEC 61000-4-2 level 3 |
| Resistance To Fast Transients | 1 kV IEC 61000-4-4 on input-output) 2 kV IEC 61000-4-4 on power supply) |
| Disturbance Radiated/Conducted | CISPR 11 CISPR 22 group 1 - class B |
| Ambient Air Temperature For Storage | -40185 °F (-4085 °C) |
| Ambient Air Temperature For Operation | 32122 °F (050 °C) mounting side by side 32140 °F (060 °C) 2 cm spacing |
| Pollution Degree | 2 IEC 60664-1 |

Ordering and shipping details

| Category | US10CP222375 | |
|-------------------|---------------|--|
| Discount Schedule | 0CP2 | |
| Gtin | 3389110109023 | |
| Returnability | No | |
| Country Of Origin | ID | |

Packing Units

| Unit Type Of Package 1 | PCE | |
|------------------------------|-------------------------|--|
| Number Of Units In Package 1 | 1 | |
| Package 1 Height | 1.06 in (2.7 cm) | |
| Package 1 Width | 3.23 in (8.2 cm) | |
| Package 1 Length | 3.35 in (8.5 cm) | |
| Package 1 Weight | 3.56 oz (101.0 g) | |
| Unit Type Of Package 2 | S02 | |
| Number Of Units In Package 2 | 47 | |
| Package 2 Height | 5.91 in (15.0 cm) | |
| Package 2 Width | 11.81 in (30.0 cm) | |
| Package 2 Length | 15.75 in (40.0 cm) | |
| Package 2 Weight | 11.55 lb(US) (5.237 kg) | |

Contractual warranty

Warranty

Apr 26, 2024

18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |


Product data sheet

RMTJ40BD

Dimensions Drawings

Analog Interface (Converter)

Dimensions




(1) Terminal block AB1TP435U or AB1RRNTP435U2

RMTJ40BD


Mounting and Clearance

Mounting

Mounting on Rails AM1 *****



Panel Mounting




Product data sheet

RMTJ40BD

Connections and Schema

Analog Interfaces

Wiring Diagram



The input, output and power supply lines must be kept away from the power cables to avoid effects due to induced interference

The supply, input and output cables must be shielded as indicated in the schemes and must be kept away from each other.