Product data sheet

Specifications





Line-Voltage Fan Coil Room Controller: BACnet MS/TP, RH sensor & control, PIR motion sensor, Silver Case/Fascia

SER8350A5B00

Product availability: Stock - Normally stocked in distribution facility

Main

Product Name	SE8000 Series	
Device Short Name	SER8300	
Product Or Component Type	Room controller	
Device Application	Line voltage fan coil	
Net Weight	11.99 oz (340 g)	
Awg Gauge	AWG 24AWG 18	
Targeted Region	North America.	
Height	4.72 in (120 mm)	
Width	3.39 in (86 mm)	
Temperature Resolution	0.1 °C	
Humidity Measurement Drift	Less Than 1 % Yearly	
Directives	2014/30/EU - electromagnetic compatibility 2014/35/EU - low voltage directive 2014/53/EU - radio equipment directive	
Line Rated Current	4 A	
Depth	0.98 in (25 mm)	
Ambient Air Temperature For Operation	32122 °F (050 °C)	
Market Segment	Lodging/Hotel Small commercial Buildings Healthcare Non-critical buildings Office Residential School	
Housing Colour	Silver	
Ambient Air Temperature For Storage	-22122 °F (-3050 °C)	
Measurement Accuracy	Temperature +/- 0.5 °C, Humidity +/- 5 %, 2080 % RH non-condensing) Humidity +/- 10 %, 1020 % non-condensing) Humidity +/- 10 %, 8090 % non-condensing)	
Information Displayed	Temperature - 40122 °F	
Network Frequency	50 Hz 60 Hz	
Communication Port Protocol BACnet MS/TP Modbus RTU		

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input Voltage	010 V DC	
Temperature Setting Range	54100 °F (1237.5 °C) cooling 4090 °F (4.532 °C) heating	
Calibration Certificate	1 Pt	
Output Voltage	24 V AC relay output 010 V DC analog output	
Relative Humidity	095 %	
Output Current	1 A relay output	
Input Type	Dry contact 2 Analog 5	
Sensor Type	10 kOhm T2 NTC thermistor Temperature Space RH sensor Humidity	
Output Type	5 xrelay output 4 xuniversal	
[Us] Rated Supply Voltage	7 V DC 50/60 Hz +/- 10 %	
Standards	EN/IEC 60730-1 FCC part 15 Subpart B ICES-003 ETSI EN 300 328 ETSI EN 301 489-1:v1.9.2 FCC part 15 Subpart C UL 60730-2-9 ETSI EN 301 489-17:v2.2.1, 2012	
Humidity Setting Range	3095 %	
Range	EcoStruxure Building Expert	
Economizer	Yes	
Humidity Control	Yes	
Pir Cover	Yes	
Scheduling	No	

Complementary

Surface Finish	Matte
Surface Treatment	Untreated
Function Available	Fan control
	HVAC control
	Available with CO2/RH/T
	Brightness sensor
	Changes can be made directly over display
	Code lock function
	Easily configurable
	Firmware update by USB

Ordering and shipping details

Category	US1DE1021009	
Discount Schedule	DE10	
Gtin	3606480772092	
Returnability	Yes	
Country Of Origin	MX	

Packing Units

	Unit Type Of Package 1	PCE
--	------------------------	-----

Number Of Units In Package 1	1
Package 1 Height	1.85 in (4.7 cm)
Package 1 Width	4.17 in (10.6 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	1.52 oz (43 g)

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: LEAD, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov