Product data sheet

Specifications



Surge protection device, Surgelogic, 80kA, 208Y/120 VAC, 3 phase, 4 wire, SPD type 1

SSP02EBA08	

() Discontinued on: Dec 4, 2020

(!) End-of-service on: Dec 31, 2020

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Surge protection device
Device Short Name	EBA

Complementary

oompiementai	y state of the second se
Voltage Rating	208Y/120 V AC
Мсоч	150 V
Sccr	200 kA
Surge Current	80 kA
Number Of Phases	3 phase
Wiring Configuration	4-wire
Connection	Wire AWG 10 copper
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault
Provided Equipment	Alarm enable/disable switch Surge counter Dry contacts
Cable Length	24 in (609.60 mm)
Device Mounting	Surface
Height	13.32 in (338.3 mm)
Width	5.74 in (145.8 mm)
Depth	4.42 in (112.3 mm)

Environment

Ambient Operating	104 °F (40 °C)
Enclosure Rating	NEMA 1
Enclosure Material	Gray painted sheet steel
Standards	CSA C22.2 No 8 UL 1449:ed. 4 UL 96A:ed. 12 UL 1283

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Category	US1DE1B08464
Discount Schedule	DE1B
Gtin	00785901557951
Returnability	No

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Weight	8.00 lb(US) (3.629 kg)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration