Product data sheet

Specifications



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product Starter Range Of Product TeSys N Current Rating 27 A Certifications UL Listed CSA Control Circuit Type Common control circuit Enclosure Type Not rated (open device) Auxiliary Contacts 1 NO + 1 NC Horsepower Rating 7.5 HP 200 V AC 7.5 HP 200 V AC 10 HP 460 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals Overload Type Solid state Motor Logic class 10/20 618 A	Mann	
Current Rating 27 A Certifications UL Listed CSA Control Circuit Type Common control circuit Enclosure Type Not rated (open device) Auxiliary Contacts 1 NO + 1 NC Horsepower Rating 7.5 HP 200 V AC 7.5 HP 200 V AC 10 HP 460 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Product	Starter
Certifications UL Listed CSA Control Circuit Type Common control circuit Enclosure Type Not rated (open device) Auxiliary Contacts 1 NO + 1 NC Horsepower Rating 7.5 HP 200 V AC 7.5 HP 200 V AC 10 HP 460 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Range Of Product	TeSys N
CSA Control Circuit Type Common control circuit Enclosure Type Not rated (open device) Auxiliary Contacts 1 NO + 1 NC Horsepower Rating 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Current Rating	27 A
Enclosure Type Not rated (open device) Auxiliary Contacts 1 NO + 1 NC Horsepower Rating 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 460 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Certifications	
Auxiliary Contacts 1 NO + 1 NC Horsepower Rating 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Control Circuit Type	Common control circuit
Horsepower Rating7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V ACNumber Of Poles3PPhase3 phaseMaximum Voltage Rating600 V AC 10 V ACNema Size1Control Circuit Voltage208 V ACStarter TypeReversingElectrical ConnectionScrew clamp terminals	Enclosure Type	Not rated (open device)
7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC Number Of Poles 3P Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Auxiliary Contacts	1 NO + 1 NC
Phase 3 phase Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Horsepower Rating	7.5 HP 230 V AC 10 HP 460 V AC
Maximum Voltage Rating 600 V AC Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Number Of Poles	3P
Nema Size 1 Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Phase	3 phase
Control Circuit Voltage 208 V AC Starter Type Reversing Electrical Connection Screw clamp terminals	Maximum Voltage Rating	600 V AC
Starter Type Reversing Electrical Connection Screw clamp terminals	Nema Size	1
Electrical Connection Screw clamp terminals	Control Circuit Voltage	208 V AC
	Starter Type	Reversing
Overload Type Solid state Motor Logic class 10/20 618 A	Electrical Connection	Screw clamp terminals
	Overload Type	Solid state Motor Logic class 10/20 618 A

Ordering and shipping details

Category	US10CP121198
Discount Schedule	0CP1
Returnability	No
Country Of Origin	US

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov