# **Product data sheet**

Specifications





# Switch body, TeSys Control, 3 poles, 125A

٧

Product availability: Stock - Normally stocked in distribution facility

Price\*: 287.00 USD

#### Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	V
Product Type	Switch body

## Complementary

<u> </u>	
Mounting Support	Symmetrical rail Plate
Performance Level	High performance
Number Of Poles	3P
Contact Type And Composition	3 NO
Network Type	AC DC
Network Frequency	50/60 Hz
[Ue] lec Rated Operational Voltage	690 V AC 50/60 Hz
lec Rated Operational Power In W	22 kW 230240 V AC-3) 30 kW 400415 V AC-3) 30 kW 690 V AC-3) 37 kW 500 V AC-3) 37 kW 690 V AC-23A) 45 kW 500 V AC-23A) 22 kW 230240 V AC-23A) 37 kW 400415 V AC-23A)
[le] Rated Operational Current	68.5 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	125 A
[Ithe] Conventional Enclosed Thermal Current	100 A
Making Capacity ( I Rms)	1250 A 400 V AC-21A 1250 A 400 V AC-22A 1250 A 400 V AC-23A
Breaking Capacity	1000 A 400 V AC-21A) 1000 A 400 V AC-22A) 1000 A 400 V AC-23A)
Rated Conditional Short Circuit Current	10 kA 400 V 125 A aM 10 kA 400 V 125 A gG
[Icm] Rated Short Circuit Making Capacity	2.8 kA 400 V at Ipeak
Intermittent Duty Class	30
Suitability For Isolation	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Icw] Rated Short-Time Withstand Rms Current	1500 A 400 V 1 s
Mechanical Durability	30000 cycles
Electrical Durability	30000 cycles AC-21 30000 cycles DC-15
lec Terminal Connection	Power circuit screw clamp terminals 0.11 in² (70 mm²) flexible - with cable end Power circuit screw clamp terminals 0.15 in² (95 mm²) solid
Tightening Torque	Power circuit 200.03 lbf.in (22.6 N.m) screw clamp terminals
Height	4.92 in (125 mm)
Width	3.54 in (90 mm)
Depth	3.54 in (90 mm)
Product Weight	1.98 lb(US) (0.9 kg)

## **Environment**

Standards	IEC 60947-3
Product Certifications	UL CSA GL UKCA
Degree Of Protection	IP20 conforming to IEC 60529
Protective Treatment	TC
Mechanical Robustness	Vibrations 10150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27
Ambient Air Temperature For Operation	-4122 °F (-2050 °C)
Fire Resistance	1760 °F (960 °C) IEC 60695-2-1

# Ordering and shipping details

Category	US10CP121730	
Discount Schedule	0CP1	
Gtin	3389110551730	
Returnability	Yes	
Country Of Origin	CZ	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.09 in (10.4 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	5.24 in (13.3 cm)
Package 1 Weight	31.85 oz (903.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	6
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)

Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	12.70 lb(US) (5.761 kg)	
Unit Type Of Package 3	P06	
Number Of Units In Package 3	96	
Package 3 Height	29.53 in (75.0 cm)	
Package 3 Width	23.62 in (60.0 cm)	
Package 3 Length	31.50 in (80.0 cm)	
Package 3 Weight	220.85 lb(US) (100.176 kg)	

# **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Toxic Heavy Metal Free
<b>②</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>②</b>	Pvc Free
<b>⊘</b>	Halogen Free Product

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations