

Product data sheet

Characteristics

VW3E704000000

module Profibus DP slave - SUBD-9 connector

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 704.97 USD



Main

Range of product	Modicon LMC078
Product or component type	Profibus DP communication module
Range compatibility	Modicon LMC078
Product compatibility	Motion controller

Complementary

Physical interface	RS485
Method of access	Slave
Integrated connection type	Profibus DP - 1 female SUB-D 9 connector, transmission rate: 12 Mbit/s

Environment


Standards	CSA C22.2 No 142 EN/IEC 61131-2 zone B UL 508
Product certifications	CE CSA cULus
Marking	CE
Ambient air temperature for operation	41...131 °F (5...55 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Relative humidity	5...95 % (without condensation)
IP degree of protection	IP20 conforming to IEC 61131-2
Pollution degree	2
Operating altitude	0...6561.68 ft (0...2000 m)
Vibration resistance	10 m/s ² with direct mounting support
Shock resistance	100 m/s ²

Ordering and shipping details

Category	18350 - PACDRIVEM
Discount Schedule	PC52
GTIN	00785901082477

Nbr. of units in pkg.	1
Package weight(Lbs)	2.2000000000000002
Returnability	N

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1801 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
----- More information	For more information go to www.p65warnings.ca.gov