# Product data sheet

Specifications





() Discontinued

## die-cast empty control station, XAPG, grey, Ø 22, 80x80mm front plate, 2 cut-outs

XAPG1502

Discontinued on: Jan 29, 2021

Main

Range Of Product   Harmony XAP     Product Or Component Type   Die-cast empty control station     Device Short Name   XAPG     Product Destination   For Ø 22 mm control and signalling units     Product Front Plate Size   80 x 80 mm     Usable Depth   2.93 in (74.5 mm)     Number Of Cut-Out   2 cut-outs     Colour Of Base Of Enclosure   Grey RAL 7032)     Colour Of Cover   Grey RAL 7032)     Material   Zinc alloy     Product Mounting   Flush mounting     Ip Degree Of Protection   IP65 IEC 60529 IP657 NF C 20-010	mann	
Device Short Name XAPG   Product Destination For Ø 22 mm control and signalling units   Product Front Plate Size 80 x 80 mm   Usable Depth 2.93 in (74.5 mm)   Number Of Cut-Out 2 cut-outs   Colour Of Base Of Enclosure Grey RAL 7032)   Colour Of Cover Grey RAL 7032)   Material Zinc alloy   Product Mounting Flush mounting   Ip Degree Of Protection IP65 IEC 60529	Range Of Product	Harmony XAP
Product Destination   For Ø 22 mm control and signalling units     Product Front Plate Size   80 x 80 mm     Usable Depth   2.93 in (74.5 mm)     Number Of Cut-Out   2 cut-outs     Colour Of Base Of Enclosure   Grey RAL 7032)     Colour Of Cover   Grey RAL 7032)     Material   Zinc alloy     Product Mounting   Flush mounting     Ip Degree Of Protection   IP65 IEC 60529	Product Or Component Type	Die-cast empty control station
Product Front Plate Size   80 x 80 mm     Usable Depth   2.93 in (74.5 mm)     Number Of Cut-Out   2 cut-outs     Colour Of Base Of Enclosure   Grey RAL 7032)     Colour Of Cover   Grey RAL 7032)     Material   Zinc alloy     Product Mounting   Flush mounting     Ip Degree Of Protection   IP65 IEC 60529	Device Short Name	XAPG
Usable Depth   2.93 in (74.5 mm)     Number Of Cut-Out   2 cut-outs     Colour Of Base Of Enclosure   Grey RAL 7032)     Colour Of Cover   Grey RAL 7032)     Material   Zinc alloy     Product Mounting   Flush mounting     Ip Degree Of Protection   IP65 IEC 60529	Product Destination	For Ø 22 mm control and signalling units
Number Of Cut-Out 2 cut-outs   Colour Of Base Of Enclosure Grey RAL 7032)   Colour Of Cover Grey RAL 7032)   Material Zinc alloy   Product Mounting Flush mounting   Ip Degree Of Protection IP65 IEC 60529	Product Front Plate Size	80 x 80 mm
Colour Of Base Of Enclosure Grey RAL 7032)   Colour Of Cover Grey RAL 7032)   Material Zinc alloy   Product Mounting Flush mounting   Ip Degree Of Protection IP65 IEC 60529	Usable Depth	2.93 in (74.5 mm)
Colour Of Cover Grey RAL 7032)   Material Zinc alloy   Product Mounting Flush mounting   Ip Degree Of Protection IP65 IEC 60529	Number Of Cut-Out	2 cut-outs
Material Zinc alloy   Product Mounting Flush mounting   Ip Degree Of Protection IP65 IEC 60529	Colour Of Base Of Enclosure	Grey RAL 7032)
Product Mounting Flush mounting   Ip Degree Of Protection IP65 IEC 60529	Colour Of Cover	Grey RAL 7032)
Ip Degree Of Protection IP65 IEC 60529	Material	Zinc alloy
	Product Mounting	Flush mounting
	p Degree Of Protection	

#### Complementary

Number Of Vertical Rows	2	
Cable Entry	0.55 in (14 mm) 1 hole with blanking plug for cable gland 0.55 in (14 mm) 1 hole without blanking plug for cable gland	
Net Weight	1.32 lb(US) (0.6 kg)	
Compatibility Code	XAPG	

#### Environment

Protective Treatment	тн
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
Electrical Shock Protection Class	Class I IEC 60536 Class I NF C 20-030

### Ordering and shipping details

Category	18406-WORLD SERVICE PARTS(OTHER OP INT)	
Discount Schedule	CS2	
Gtin	3389118115774	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Returnability	No
---------------	----

#### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.74 in (9.5 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	3.54 in (9 cm)
Package 1 Weight	25.54 oz (724 g)

# **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov