# **Product data sheet**

Specifications





Pilot light, Harmony XB4, incandescent light, white, 22mm, with plain lens, BA9s bulb, 110…120V

XB4BV31

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 128.70 USD

#### Main

Range Of Product	Harmony XB4		
Product Or Component Type	Pilot light		
Device Short Name	XB4		
Bezel Material	Chromium plated metal		
Fixing Collar Material	Zamak		
Head Type	Standard		
Mounting Diameter	0.89 in (22.5 mm)		
Sale Per Indivisible Quantity	1		
Shape Of Signaling Unit Head	Round		
Cap/Operator Or Lens Colour	White		
Operator Additional Information	With plain lens		
Light Source	Incandescent		
Bulb Base	BA 9s		
Light Block Supply	Via integral transformer 1.2 VA 6 V		
[Us] Rated Supply Voltage	110120 V AC 50/60 Hz		

### Complementary

Height	1.85 in (47 mm)				
Width	1.18 in (30 mm)				
Depth	3.07 in (78 mm)				
Terminals Description Iso N°1	(X1-X2)PL				
Net Weight	0.34 lb(US) (0.152 kg)				
Resistance To High Pressure Washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m				
Connections - Terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1 Screw clamp terminals, 1 x 0.222 x 2.5 mm² without cable end IEC 60947-1				
[Ui] Rated Insulation Voltage	600 V 3)IEC 60947-1				
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947-1				
Signalling Type	Steady				
Device Presentation	Complete product				

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

### **Environment**

Protective Treatment	тн			
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)			
Ambient Air Temperature For Operation	-40131 °F (-4055 °C)			
Electrical Shock Protection Class	Class I IEC 60536			
Ip Degree Of Protection	IP66 IEC 60529 IP67 IP69 IP69K			
Nema Degree Of Protection	NEMA 13 NEMA 4X			
Ik Degree Of Protection	IK06 conforming to IEC 50102			
Standards	IEC 60947-5-4 IEC 60947-5-5 IEC 60947-5-1 UL 508 JIS C8201-5-1 IEC 60947-1 CSA C22.2 No 14 JIS C8201-1			
Product Certifications	UL Listed CSA			
Vibration Resistance	5 gn 12500 Hz)IEC 60068-2-6			
Shock Resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27			

# Ordering and shipping details

Category	US10CS222468		
Discount Schedule	0CS2		
Gtin	3389110887211		
Returnability	No		
Country Of Origin	MX		

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.26 in (3.2 cm)
Package 1 Width	2.05 in (5.2 cm)
Package 1 Length	3.23 in (8.2 cm)
Package 1 Weight	5.11 oz (145.0 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	3.46 in (8.8 cm)
Package 2 Width	1.34 in (3.4 cm)
Package 2 Length	10.43 in (26.5 cm)
Package 2 Weight	25.68 oz (728.0 g)
Unit Type Of Package 3	S02

Number Of Units In Package 3	50
Package 3 Height	5.91 in (15.0 cm)
Package 3 Width	11.81 in (30.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	17.07 lb(US) (7.741 kg)

## **Contractual warranty**

Warranty 18 months

### Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information


Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration			
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)			
China Rohs Regulation	China RoHS declaration			
<b>Environmental Disclosure</b>	Product Environmental Profile			
	The product must be disposed on European Union markets following specific was collection and never end up in rubbish bins.			
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.			
Weee Circularity Profile	· · · · · · · · · · · · · · · · · · ·			

### **Dimensions Drawings**

### **Dimensions**



e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.

- · · · · · · · · · · · · · · · · · · ·					
a in mm	a in in.	b in mm	b in in.	c in mm	c in in.
66	2.60	30	1.18	46.5	1.83


### **XB4BV31**


#### Mounting and Clearance

#### Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Clamp Terminals or Plug-in **Connectors or on Printed Circuit Board** 

**Connection by Faston Connectors** 





- (1) Diameter on finished panel or support
- (2) 40 mm min. / 1.57 in. min.
- (3) 30 mm min. / 1.18 in. min.
- (4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm  $_0^{+0.4}$  / 0.88 in.  $_0^{+0.016}$ )
- (5) 45 mm min. / 1.78 in. min.
- (6) 32 mm min. / 1.26 in. min.