Product data sheet Characteristics

XUSLZD71360

protection tube - safety light curtain type 4 - acrylic - 1362 mm - IP67

Price*: 1,650.00 USD



XUSLZD71360 has not been replaced. Please contact your customer care center for more information.

Range of product	Preventa Safety detection	
Accessory / separate part designation	IP67 protection tube	7
Accessory / separate part type	Protection tube	
Accessory / separate part category	Protection accessories	
Product compatibility	XUSLB1360 XUSLDS1360 XUSLDM1360	products for
Accessory / separate part destination	Safety light curtain type 4	94
Quantity per set	Set of 2	

Complementary

Complementary	
Height	53.62 in (1362 mm)
Material	Acrylic
Sensing distance reduction coefficient	0.90 Sn
Product weight	15.01 lb(US) (6.81 kg)

Environment

IP degree of protection	IP67 conforming to IEC 60529	
Resistance to chemical agents	Resistant detergents and cleaners	
	Resistant aqueous solutions	
	Limited resistant against chlorinated or aromatic hydrocarbons	
	Resistant to inorganic diluted acids	
	Resistant aliphatic hydrocarbons	
	Limited resistant against ketones	
	Resistant alkalis	
	Limited resistant against esters	
Environmental characteristic	UV resistant	
	Adverse weather resistant	
	Humidity resistant	
	Resistant against immersion in water	
Ambient air temperature for operation	32104 °F (040 °C)	
Ambient air temperature for storage	-13158 °F (-2570 °C)	

Ordering and shipping details

Category	22455 - LIGHT CURTAINS - XUSL
Discount Schedule	DS2
Nbr. of units in pkg.	1
Package weight(Lbs)	11.55000000000001
Returnability	N
Country of origin	US

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0947 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity

Contractual warranty

	Warranty period	18 months
--	-----------------	-----------