

# Product data sheet

Specifications



## gateway module - for As-I line - Modbus Plus - RS485

XZML16222

! Discontinued

### Main

Range Of Product	AS-Interface cabling system
Product Or Component Type	Gateway module
Communication Port Protocol	Modbus Plus
Communication Port Support	RS485
Supply	Via AS-Interface line

### Complementary

Actuator Sensor Interface Profile [As-I]	M1
Number Of Server Device(S)	31 AS-Interface line)
Electrical Connection	1 connector SUB-D 9 supervisory line Screw terminals 2 x 1.5 mm² with cable end AS-Interface line
Transmission Rate	1 Mbit/s supervisory line
Number Of Addresses	64
Maximum Supply Current	0.2 A
Monitoring Function	Diagnostics done by the line
Local Signalling	1 display, 2 x 7 segments diagnostics and maintenance LED diagnostics and maintenance
Fixing Mode	By screws (panel) Clip-on (35 mm symmetrical DIN rail)
Net Weight	0.99 lb(US) (0.45 kg)

### Environment

Product Certifications	AS-Interface No 04601
Ambient Air Temperature For Operation	32...131 °F (0...55 °C)
Ambient Air Temperature For Storage	-13...185 °F (-25...85 °C)
Ip Degree Of Protection	IP20
Vibration Resistance	1 gn 2...150 Hz)IEC 60068-2-6
Shock Resistance	30 gn 11 ms IEC 60068-2-27

### Ordering and shipping details

Category	18325-SERIPLEX SOFTWARE&CABLES DISC SPX2
Discount Schedule	SPX2

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Gtin	3389110775235
Returnability	No
Country Of Origin	DE

## Contractual warranty

Warranty	18 months
----------	-----------