Product data sheet

Specifications





Contact block, Harmony XAL, XAPS, single contact, silver alloy, rear mounting, screw clamp terminal, 1NO

ZENL1111TQ

Product availability: Stock - Normally stocked in distribution facility

Price*: 16.40 USD

Main

Range Of Product	Harmony XAL Harmony XAPS	
Product Or Component Type	Contact block	
Device Short Name	ZENL	
Product Destination	For XB5 Ø 22 mm control and signalling units For XAPS control station	
Mounting Of Block	Rear mounting	
Sale Per Indivisible Quantity	100	
Contacts Type And Composition	1 NO	

Complementary

Assembly Style	For customer assembly	
Contact Operation	Slow-break	
Positive Opening	Without	
Operating Travel	0.10 in (2.6 mm) NO changing electrical state) 0.17 in (4.3 mm) total travel)	
Operating Force	2.3 N NO changing electrical state	
Operating Torque	0.44 lbf.in (0.05 N.m) NO changing electrical state	
Mechanical Durability	10000000 cycles	
Connections - Terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1 Screw clamp terminals, >= 1 x 0.22 mm² without cable end IEC 60947-1	
Tightening Torque	7.0810.62 lbf.in (0.81.2 N.m) IEC 60947-1	
Shape Of Screw Head	Cross Philips no 1 Cross pozidriv No 1 Slotted flat Ø 4 mm Slotted flat Ø 5.5 mm	
Contacts Material	Silver alloy (Ag/Ni)	
Maximum Resistance Across Terminals	25 MOhm	
Short-Circuit Protection	10 A cartridge fuse gG IEC 60947-5-1	
[Ith] Conventional Free Air Thermal Current		
[Ui] Rated Insulation Voltage	Insulation Voltage 600 V 3)IEC 60947-1	
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947-1	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[le] Rated Operational Current	3 A 240 V, AC-15, A600 IEC 60947-5-1 6 A 120 V, AC-15, A600 IEC 60947-5-1 0.1 A 600 V, DC-13, Q600 IEC 60947-5-1 0.27 A 250 V, DC-13, Q600 IEC 60947-5-1 0.55 A 125 V, DC-13, Q600 IEC 60947-5-1 1.2 A 600 V, AC-15, A600 IEC 60947-5-1
Electrical Durability	1000000 cycles, AC-15, 2 A 230 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A 120 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 4 A 24 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.2 A 110 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.5 A 24 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C
Electrical Reliability	Λ < 10exp(-6) 5 V 1 mA in clean environment IEC 60947-5-4 Λ < 10exp(-8) 17 V 5 mA IEC 60947-5-4
Additional Information	Mounting on integrated plate in the box
Electrical Composition Code	SR1 3) SR2 2) MR1 2)

Environment

Protective Treatment	тн	
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)	
Ambient Air Temperature For Operation	-40158 °F (-4070 °C)	
Ip Degree Of Protection	IP20 IEC 60529	
Standards	IEC 60947-5-1 IEC 60947-1 CSA C22.2 No 14 JIS C8201-5-1 IEC 60947-5-4 IEC 60947-5-5 UL 508 JIS C8201-1	
Vibration Resistance	5 gn 12500 Hz)IEC 60068-2-6	
Shock Resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	

Ordering and shipping details

Category	US10CS222475	
Discount Schedule	0CS2	
Gtin	3389110960341	
Returnability	Yes	
Country Of Origin	FR	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.13 in (5.4 cm)
Package 1 Width	2.20 in (5.6 cm)
Package 1 Length	1.73 in (4.4 cm)
Package 1 Weight	0.53 oz (15.0 g)
Unit Type Of Package 2	CAR
Number Of Units In Package 2	100

Package 2 Height	2.13 in (5.4 cm)
Package 2 Width	2.20 in (5.6 cm)
Package 2 Length	1.73 in (4.4 cm)
Package 2 Weight	7.05 oz (200.0 a)

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
Ø	Mercury Free	
Ø	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov